

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER VARIATOR, NEW UNICA, ROTARY PUSH TYPE, ALUMINIU

Schneider Electric New Unica dimmer NU351430 is a mechanism in color aluminium with 2 modules. In addition, the rated operational voltage of this device is 230V. And the dimmer's associated fuse rating is 16. And the control type of this dimmer is local control, remote control by auxiliary push-button. Its protection type is automatic overload protection, overheating protection, short-circuit protection, taking care of your safety as much as possible. Its matching mounting box can be recessed into the surface of the wall with flush type. The connection terminals of this dimmer are screw terminal. What's more, its directives are 2014/30/EU - electromagnetic compatibility, 2014/35/EU - low voltage directive. It is 45 mm in width, 45 mm in height, 47 mm in depth, and with an embedding depth of 29 mm. And the product weighs 0.129 kg. The IP rating of this device is IP20, IP21. It obtained CE, EAC, FIMKO, NEMKO, NF, SEMKO, VDE certificate as well. What's more, it well satisfied the standard of EN 300-328, EN 301-489-17, EN 60669-2-1, EN 60730-2-7. And it is mercury free Being environmentally friendly, this dimmer is a green premium product too. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main Product brand - Schneider Electric

Range - New Unica

Type number - NH3514

Product or component type - Dimmer

Complementary

device presentation - Mechanism

Device application - Light control

Dimmer type - Universal

Dimmer control - Rotary push type

Load type - Incandescent lamp: 5...200 W at 230 V AC

Halogen lamp: 5...150 W at 230 V AC

LED lamp: 5...100 VA at 230 V AC (RC LED mode)

LED lamp: 5...20 VA at 230 V AC (RL LED mode)

LV halogen lamps: 5...150 VA at 12 V AC (electronic transformer)

LV halogen lamps: 5...150 VA at 12 V AC (wound transformer)

Function available - With memory function

[Ue] rated operational voltage - 230 V AC 50 Hz

Associated fuse rating - 16 A

Protection type - Overheating protection

Automatic overload protection

Short-circuit protection

colour - Aluminium

Surface finish - Painted powder coated

Number of modules - 2 modules

Number of outputs - 1

Control type - Local control dimming up/down control

Local control automatic load detection

Remote control by auxiliary push-button

Connected auxiliaries - Unlimited number of push-buttons, distance : 50 m

Provided equipment - User manual

Connections - terminals - Screw terminal

Number of loop terminals - 2

Clamping connection capacity - 1.5...2.5 mmA² for solid cable(s)

1.5...2.5 mmA² for solid stranded cable(s)

Shape of screw head - Pozidriv No 1 and combi

Tightening torque - 0.5 N.m

Material - PC (polycarbonate) GF10 FR: casing

Metal: terminals

Thermoplastic ABS-UV stabilised: central plate

device mounting - Flush

Fixing mode - By screws

Type of installation - Indoor installation

Quantity per set - 1 carton

Embedding depth - 29 mm

Depth - 47 mm

Width - 45 mm

Height - 45 mm

Net weight - 0.129 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

Ambient air temperature for operation - 5a€|40 A°C
Ambient air temperature for storage - 5a€|40 A°C
IP degree of protection - IP20
IP21 with marking on visual parts
IK degree of protection - IK04
Environmental characteristic - Petrol
Alcohol
Oil
Liquid soap
Window-cleaning fluid
UV resistant
Bleach
Acetone
Standards - EN 300-328
EN 60669-2-1
EN 60730-2-7
EN 301-489-17
Directives - 2014/30/EU - electromagnetic compatibility
2014/35/EU - low voltage directive
Product certifications - SEMKO
VDE
FIMKO
EAC
CE
NEMKO
NF
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 7.8 cm
Package 1 Width - 9.6 cm
Package 1 Length - 9.6 cm
Package 1 Weight - 111 g
Unit Type of Package 2 - S01
Number of Units in Package 2 - 4
Package 2 Height - 15 cm
Package 2 Width - 15 cm
Package 2 Length - 40 cm
Package 2 Weight - 653 g
Unit Type of Package 3 - P06
Number of Units in Package 3 - 128
Package 3 Height - 77 cm
Package 3 Width - 80 cm
Package 3 Length - 60 cm
Package 3 Weight - 32.82 kg
Pret: 545,21 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/variator-new-unica-rotary-push-type-aluminiu-319200>