

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER VARIATOR, NEW UNICA, WISER, ROTARY PUSH TYPE, ALB

Schneider Electric New Unica dimmer NU551418 is a mechanism with fixing frame in color white with 2 modules. 230V is the rated operational voltage. And the dimmer's associated fuse rating is 16. And the control type of this dimmer is local control, remote control by auxiliary push-button. Its protection type is automatic overload protection, overheating protection, short-circuit protection, taking care of your safety as much as possible. Its matching mounting box can be recessed into the surface of the wall with flush type. Its connection terminals are screw terminal. What's more, its directives are 2014/30/EU - electromagnetic compatibility, 2014/35/EU - low voltage directive. It is 74.5 mm in width, 74.5 mm in height, 47 mm in depth, and with an embedding depth of 29 mm. And the product weighs 0.129 kg. Besides, the IP rating of this device is IP20. It obtained CE, EAC, FIMKO, NEMKO, NF, SEMKO, VDE certificate as well. What's more, it well satisfied the standard of EN 300-328, EN 301-489-17, EN 60669-2-1, EN 60730-2-7. And it is mercury free What's more, this device is qualified as a green premium product, with minimal use of hazardous substances. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements.

Main
Product brand - Schneider Electric
Range - New Unica
Type number - NH3514
Product or component type - Connected dimmer
Complementary
Concentrator compatibility - Wiser hub generation 1
Mobile App name - Wiser by SE
device presentation - Mechanism with fixing frame
Device application - Light control
Dimmer type - Universal
Dimmer control - Rotary push type
Load type - Incandescent lamp: 5...200 W at 230 V AC
Halogen lamp: 5...150 W at 230 V AC
LED lamp: 5...100 VA at 230 V AC (RC LED mode)
LED lamp: 5...20 VA at 230 V AC (RL LED mode)
LV halogen lamps: 5...150 VA at 12 V AC (electronic transformer)
LV halogen lamps: 5...150 VA at 12 V AC (wound transformer)
Function available - With memory function
[Ue] rated operational voltage - 230 V AC 50 Hz
Associated fuse rating - 16 A
Protection type - Short-circuit protection
Automatic overload protection
Overheating protection
colour - White (RAL 9003)
Surface finish - Glossy
Number of modules - 2 modules
Number of outputs - 1
Control type - Local control dimming up/down control
Local control automatic load detection
Remote control by auxiliary push-button
Communication network type - Wireless Zigbee (2.4 GHz), 2.5 mW at < 50 m
Connected auxiliaries - Unlimited number of push-buttons, distance : 50 m
Provided equipment - Fixing frame
User manual
Connections - terminals - Screw terminal
Number of loop terminals - 2
Clamping connection capacity - 1.5...2.5 mm² for solid cable(s)
1.5...2.5 mm² for solid stranded cable(s)
Shape of screw head - Pozidriv No 1 and combi
Tightening torque - 0.5 N.m
Material - PC (polycarbonate) GF10 FR: casing
Metal: terminals
Thermoplastic ABS-UV stabilised: central plate
Zamak: fixing frame
device mounting - Flush
Fixing mode - By screws
Type of installation - Indoor installation
Quantity per set - 1 carton
Embedding depth - 29 mm
Depth - 47 mm
Width - 74.5 mm
Height - 74.5 mm
Net weight - 0.129 kg
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach

Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
Ambient air temperature for operation - 5a€|40 A°C
Ambient air temperature for storage - 5a€|40 A°C
IP degree of protection - IP20
IK degree of protection - IK04
Environmental characteristic - Petrol
Acetone
Window-cleaning fluid
UV resistant
Oil
Liquid soap
Bleach
Alcohol
Standards - EN 301-489-17
EN 60730-2-7
EN 300-328
EN 60669-2-1
Directives - 2014/35/EU - low voltage directive
2014/30/EU - electromagnetic compatibility
Product certifications - NEMKO
NF
SEMKO
EAC
VDE
CE
FIMKO
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 7.5 cm
Package 1 Width - 9.5 cm
Package 1 Length - 9.5 cm
Package 1 Weight - 121.0 g
Unit Type of Package 2 - S02
Number of Units in Package 2 - 9
Package 2 Height - 15.0 cm
Package 2 Width - 30.0 cm
Package 2 Length - 40.0 cm
Package 2 Weight - 1.308 kg
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/variator-new-unica-wiser-rotary-push-type-alb-319202>