


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER VARIATOR, NEW UNICA, WISER HOME, LED, ALB

Main

Product brand - Schneider Electric

Range - New Unica

Type number - NH3515

Product or component type - Connected dimmer

Complementary

Concentrator compatibility - Wiser hub generation 1

Wiser hub generation 2

Mobile App name - Wiser Home

device presentation - Mechanism

Device application - Light control

Dimmer type - Universal

Dimmer control - Push type

Load type - Incandescent lamp: 14...200 W at 230 V AC

Halogen lamp: 14...150 W at 230 V AC

LV halogen lamps: 14...150 VA at 12 V AC (wound transformer)

LED lamp: 7...100 VA at 230 V AC (RC LED mode)

LED lamp: 7...20 VA at 230 V AC (RL LED mode)

LV halogen lamps: 14...150 VA at 12 V AC (electronic transformer)

[Ue] rated operational voltage - 230 V AC 50 Hz

Standby consumption - Max. 0.4 W

Associated fuse rating - 16 A

Protection type - Short-circuit protection

Overheating protection

Automatic overload protection

colour - White (RAL 9003)

Surface finish - Glossy

Number of modules - 2 modules

Number of FUNCTION keys - 2

Local signalling - Programmable: 1 LED (green/red)

Signalling function - Locator

Programming indication

Light ON when switch is actuated

Number of outputs - 1

Control type - Local control dimming up/down control

Local control automatic load detection

Remote control by auxiliary push-button on/off switching

Remote control by auxiliary push-button dimming up/down control

Remote control Wiser App on/off switching

Remote control Wiser App dimming up/down control

Local control on/off switching

Remote control Wiser App device programming

Local control soft start

Software name - Wiser App: dimming range control

Wiser App: overtravel control

Wiser App: program the switching time

Wiser App: enable timer mode

Wiser App: management of the dimming mode

Wiser App: enable switch-on brightness/memory function

Wiser App: enable timer mode/overtravel time

Wiser App: upgrade device firmware

Wiser App: load control

Wiser App: define LED status

Wiser App: management of trigger settings

Wiser App: weekday switching

Wiser App: astro function

Wiser App: random function

Wiser App: enable wake-up function

Wiser App: light control

Wiser App: enable fall-asleep function

Wiser App: starting staircase timer (with/without warning)

Time delay range - 1 s...24 h (overtravel)

Maximum number of connected devices - Zigbee: 15 (smart device)

10 (Wiser device)

10 (multiway switching between coupled device)

Communication network type - Wireless Zigbee (2.4 GHz), 2.5 mW at < 50 m

System requirements - Wiser Home Touch Wiser App

Wiser Home Touch Wiser Home control Bluetooth

Wiser Home Touch Wiser Home control

Connected auxiliaries - Unlimited number of push-buttons, distance : 50 m

Provided equipment - User manual

Connections - terminals - Screw terminal

Number of loop terminals - 2

Clamping connection capacity - 1.5...2.5 mm² for solid cable(s)

1.5...2.5 mm² for solid stranded cable(s)

Shape of screw head - Pozidriv No 1 and combi

Tightening torque - 0.5 N.m

Material - PC (polycarbonate) GF10 FR: casing
Metal: terminals
Thermoplastic ABS-UV stabilised: central plate
Mounting support - Wall
device mounting - Flush
Fixing mode - By screws
Type of installation - Indoor installation
Quantity per set - 1 carton
Embedding depth - 29 mm
Depth - 41 mm
Width - 45 mm
Height - 45 mm
Net weight - 0.11 kg
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
Ambient air temperature for operation - 5a€|40 A°C
Ambient air temperature for storage - 5a€|40 A°C
IP degree of protection - IP20
IP21 with marking on visual parts
IK degree of protection - IK04
Environmental characteristic - Bleach
UV resistant
Petrol
Alcohol
Oil
Acetone
Window-cleaning fluid
Liquid soap
Standards - EN 60669-2-1
EN 301-489-17
EN 300-328
EN 60730-2-7
Directives - 2014/35/EU - low voltage directive
2014/30/EU - electromagnetic compatibility
Product certifications - CE
EAC
NEMKO
SEMKO
NF
FIMKO
VDE
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 7.9 cm
Package 1 Width - 9.6 cm
Package 1 Length - 9.6 cm
Package 1 Weight - 119.0 g
Unit Type of Package 2 - S02
Number of Units in Package 2 - 9
Package 2 Height - 15.0 cm
Package 2 Width - 30.0 cm
Package 2 Length - 40.0 cm
Package 2 Weight - 1.372 kg
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/variator-new-unica-wiser-home-led-alb-319212>