

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER VARIATOR, NEW UNICA, CU RAMA FIXARE, ROTARY PUSH TYPE, ANTRACIT

Schneider Electric New Unica dimmer NU551454D is a mechanism with fixing frame in color anthracite with 2 modules. In addition, the rated operational voltage of this device is 230V. And the associated fuse rating is 16. And the control type of this dimmer is local control, remote control by auxiliary push-button. Its protection type is automatic overload protection, overheating protection, short-circuit protection, taking care of your safety as much as possible. Its matching mounting box can be recessed into the surface of the wall with flush type. Its connection terminals are screw terminal. What's more, its directives are 2014/30/EU - electromagnetic compatibility, 2014/35/EU - low voltage directive. It is 74.5 mm in width, 74.5 mm in height, 47 mm in depth, and with an embedding depth of 29 mm. And the product weighs 0.129 kg. It reaches IP20 degree of protection too. It obtained CE, EAC, FIMKO, NEMKO, NF, SEMKO, VDE certificate as well. What's more, it well satisfied the standard of EN 300-328, EN 301-489-17, EN 60669-2-1, EN 60730-2-7. And it is mercury free Being environmentally friendly, this dimmer is a green premium product too. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main Product brand - Schneider Electric

Range - New Unica

Type number - NH3514

Product or component type - Dimmer

Complementary

device presentation - Mechanism with fixing frame

Device application - Light control

Dimmer type - Universal

Dimmer control - Rotary push type

Load type - Incandescent lamp: 5...200 W at 230 V AC

Halogen lamp: 5...150 W at 230 V AC

LED lamp: 5...100 VA at 230 V AC (RC LED mode)

LED lamp: 5...20 VA at 230 V AC (RL LED mode)

LV halogen lamps: 5...150 VA at 12 V AC (electronic transformer)

LV halogen lamps: 5...150 VA at 12 V AC (wound transformer)

Function available - With memory function

[Ue] rated operational voltage - 230 V AC 50 Hz

Associated fuse rating - 16 A

Protection type - Automatic overload protection

Overheating protection

Short-circuit protection

colour - Anthracite (RAL 7021)

Surface finish - Painted powder coated

Number of modules - 2 modules

Number of outputs - 1

Control type - Local control dimming up/down control

Local control automatic load detection

Remote control by auxiliary push-button

Connected auxiliaries - Unlimited number of push-buttons, distance : 50 m

Provided equipment - Fixing frame

User manual

Connections - terminals - Screw terminal

Number of loop terminals - 2

Clamping connection capacity - 1.5...2.5 mm² for solid cable(s)

1.5...2.5 mm² for solid stranded cable(s)

Shape of screw head - Pozidriv No 1 and combi

Tightening torque - 0.5 N.m

Material - PC (polycarbonate) GF10 FR: casing

Metal: terminals

Thermoplastic ABS-UV stabilised: central plate

Zamak: fixing frame

device mounting - Flush

Fixing mode - By screws

Type of installation - Indoor installation

Quantity per set - 1 carton

Embedding depth - 29 mm

Depth - 47 mm

Width - 74.5 mm

Height - 74.5 mm

Net weight - 0.129 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane
Environment
Ambient air temperature for operation - 5a€|40 A°C
Ambient air temperature for storage - 5a€|40 A°C
IP degree of protection - IP20
IK degree of protection - IK04
Environmental characteristic - Alcohol
Petrol
UV resistant
Bleach
Oil
Window-cleaning fluid
Acetone
Liquid soap
Standards - EN 301-489-17
EN 60669-2-1
EN 60730-2-7
EN 300-328
Directives - 2014/30/EU - electromagnetic compatibility
2014/35/EU - low voltage directive
Product certifications - EAC
SEMKO
CE
NEMKO
NF
FIMKO
VDE
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 7.7 cm
Package 1 Width - 9.5 cm
Package 1 Length - 9.5 cm
Package 1 Weight - 125.0 g
Unit Type of Package 2 - S01
Number of Units in Package 2 - 4
Package 2 Height - 15 cm
Package 2 Width - 15 cm
Package 2 Length - 40 cm
Package 2 Weight - 665 g
Unit Type of Package 3 - P06
Number of Units in Package 3 - 128
Package 3 Height - 77 cm
Package 3 Width - 80 cm
Package 3 Length - 60 cm
Package 3 Weight - 29.78 kg
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/variator-new-unica-cu-rama-fixare-rotary-push-type-antracit-319220>