



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov Banca: BRD IBAN: RO34BRDE441SV13182234410



SCHNEIDER PLACA ORNAMENT, UNICA STUDIO, UN MODUL, ANTRACIT

Schneider Electric New Unica cover frame NU200254 is in color anthracite The cover frame is made of thermoplastic ABS-UV stabilised, making it as resistant as possible. This cover frame has 1 gang Besides, it reaches IK04 protection level, which can help protect against impact. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. This cover frame is SVHC (substances of very high concern) free too. This cover frame belongs to Unica Studio aesthetic group. What's more, it well satisfied the standard of IEC 60669-1, IEC 60884-1. It is 85 mm in width. 85 mm in height. 10 mm in depth. Besides it is halogen free halogen free, which is good for your health. With 2 modules. The fixing mode of this device is clip-in. And the product weighs 0.013 kg. Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements.Main Range - New Unica Device application - Mounting Product or component type - Cover frame aesthetic name - Unica Studio Number of gangs - 1 gang Installation direction - Horizontal/vertical Type of frame - Single Number of modules - 2 modules Fixing mode - Clip-in Colour tint - Anthracite (RAL 7021) Complementary Material - Thermoplastic ABS-UV stabilised: cover frame Standards - IEC 60884-1 IEC 60669-1 Width - 85 mm Height - 85 mm Depth - 10 mm Net weight - 0.013 kg Resistance to chemical agents - Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane Environment IK degree of protection - IK04 IP degree of protection - IP21D Packing Units Unit Type of Package 1 - PCE Number of Units in Package 1 - 1 Package 1 Height - 1 cm Package 1 Width - 8.5 cm Package 1 Length - 8.5 cm Package 1 Weight - 13 g Unit Type of Package 2 - BB1 Number of Units in Package 2 - 10 Package 2 Height - 10.4 cm Package 2 Width - 11.5 cm Package 2 Length - 12 cm Package 2 Weight - 201 g Unit Type of Package 3 - S04 Number of Units in Package 3 - 300 Package 3 Height - 30 cm Package 3 Width - 40 cm Package 3 Length - 60 cm Package 3 Weight - 7.048 kg Pret: 9,91 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/placa-ornament-unica-studio-un-modulantracit-319247