


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER PLACA ORNAMENT, UNICA STUDIO COLSAU, TREI MODULE, TAUPE

Schneider Electric New Unica cover frame NU280626 is in color taupe Being made of polycarbonate, thermoplastic ABS-UV stabilised material, this cover frame is quite reliable and resistant. This cover frame has 3 gangs Besides, it reaches IK04 protection level, which can help protect against impact. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. This cover frame is SVHC (substances of very high concern) free too. This cover frame belongs to Unica Studio Color aesthetic group. What's more, it well satisfied the standard of IEC 60669-1, IEC 60884-1. It is 227 mm in width. 85 mm in height. 10 mm in depth. Besides it is halogen free halogen free, which is good for your health. With 3 x 2 modules. The fixing mode of this device is clip-in. And the product weighs 0.047 kg. New Unica features innovative functions to carry the range into the smart homes of the future. Welcome to the new Unica æ" irresistible, beautiful, and innovative. Main

Range - New Unica

Device application - Mounting

Product or component type - Cover frame

aesthetic name - Unica Studio Color

Number of gangs - 3 gangs

Installation direction - Horizontal/vertical

Type of frame - Triple

Number of modules - 3 x 2 modules

Fixing mode - Clip-in

Colour tint - Taupe

side color - White (RAL 9003)

Complementary

Material - Thermoplastic ABS-UV stabilised: cover frame

Polycarbonate: intermediate plate

Standards - IEC 60884-1

IEC 60669-1

Width - 227 mm

Height - 85 mm

Depth - 10 mm

Net weight - 0.047 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK04

IP degree of protection - IP21D

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 1 cm

Package 1 Width - 8.5 cm

Package 1 Length - 22.7 cm

Package 1 Weight - 51 g

Unit Type of Package 2 - BB1

Number of Units in Package 2 - 5

Package 2 Height - 5.6 cm

Package 2 Width - 10.8 cm

Package 2 Length - 24.7 cm

Package 2 Weight - 297 g

Unit Type of Package 3 - S04

Number of Units in Package 3 - 150

Package 3 Height - 30 cm

Package 3 Width - 40 cm

Package 3 Length - 60 cm

Package 3 Weight - 10.15 kg

Pret: 39,59 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/placa-ornament-unica-studio-colsau-trei-module-taupe-319316>