

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER PLACA ORNAMENT, UNICA PRO, UN MODUL, ANTRACIT

Schneider Electric New Unica cover frame NU400254 is in color anthracite Being made of polycarbonate, thermoplastic ABS-UV stabilised material, this cover frame is quite reliable and resistant. This cover frame has 1 gang Besides, it reaches IK04 protection level, which can help protect against impact. Also, it is environment-friendly, with UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid reached. This cover frame is SVHC (substances of very high concern) free too. This cover frame belongs to Unica Pro aesthetic group. What's more, it well satisfied the standard of IEC 60669-1, IEC 60884-1. It is 85 mm in width. 85 mm in height. 10 mm in depth. Besides it is halogen free halogen free, which is good for your health. With 1 x 2 modules. The fixing mode of this device is clip-in. And the product weighs 0.018 kg. New Unica features innovative functions to carry the range into the smart homes of the future. Welcome to the new Unica a€" irresistible, beautiful, and innovative. Main

Range - New Unica

Device application - Mounting

Product or component type - Cover frame

aesthetic name - Unica Pro

Number of gangs - 1 gang

Installation direction - Horizontal/vertical

Type of frame - Single

Number of modules - 2 modules

Fixing mode - Clip-in

Colour tint - Anthracite (RAL 7021)

Complementary

Material - Thermoplastic ABS-UV stabilised: cover frame

Polycarbonate: intermediate plate

Standards - IEC 60884-1

IEC 60669-1

Width - 85 mm

Height - 85 mm

Depth - 10 mm

Net weight - 0.018 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK04

IP degree of protection - IP21D

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 8.5 cm

Package 1 Width - 8.5 cm

Package 1 Length - 1.0 cm

Package 1 Weight - 19.0 g

Unit Type of Package 2 - BB1

Number of Units in Package 2 - 10

Package 2 Height - 11.5 cm

Package 2 Width - 10.5 cm

Package 2 Length - 12.0 cm

Package 2 Weight - 226.0 g

Unit Type of Package 3 - S04

Number of Units in Package 3 - 300

Package 3 Height - 30.0 cm

Package 3 Width - 40.0 cm

Package 3 Length - 60.0 cm

Package 3 Weight - 7.55 kg

Pret: 10,15 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/placa-ornament-unica-pro-un-modul-antracit-319337>