

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **SCHNEIDER PLACA ORNAMENT, UNICA PRO, UN MODUL, ALUMINIU**

Schneider Electric New Unica cover frame NU411630 is in color aluminium Being made of polycarbonate, thermoplastic ABS-UV stabilised material, this cover frame is quite reliable and resistant. This cover frame has 1 gang Besides, it reaches IK04 protection level, which can help protect against impact. Also, it is environment-friendly, with UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid reached. This cover frame is SVHC (substances of very high concern) free too. This cover frame belongs to Unica Pro aesthetic group. What's more, it well satisfied the standard of IEC 60669-1, IEC 60884-1. It is 227 mm in width. 85 mm in height. 10 mm in depth. Besides it is halogen free halogen free, which is good for your health. With 6 modules. The fixing mode of this device is clip-in. And the product weighs 0.04 kg. New Unica features innovative functions to carry the range into the smart homes of the future. Welcome to the new Unica a€" irresistible, beautiful, and innovative. Main

Range - New Unica

Device application - Mounting

Product or component type - Cover frame

aesthetic name - Unica Pro

Number of gangs - 1 gang

Installation direction - Horizontal

Type of frame - Single

Number of modules - 6 modules

Fixing mode - Clip-in

Colour tint - Aluminium

Complementary

Material - Thermoplastic ABS-UV stabilised: cover frame

Polycarbonate: intermediate plate

Standards - IEC 60884-1

IEC 60669-1

Width - 227 mm

Height - 85 mm

Depth - 10 mm

Net weight - 0.04 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK04

IP degree of protection - IP21D

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 1.000 cm

Package 1 Width - 8.500 cm

Package 1 Length - 23.000 cm

Package 1 Weight - 42.000 g

Unit Type of Package 2 - BB1

Number of Units in Package 2 - 5

Package 2 Height - 6.000 cm

Package 2 Width - 11.000 cm

Package 2 Length - 25.000 cm

Package 2 Weight - 271.000 g

Unit Type of Package 3 - S01

Number of Units in Package 3 - 10

Package 3 Height - 15.000 cm

Package 3 Width - 15.000 cm

Package 3 Length - 40.000 cm

Package 3 Weight - 743.000 g

Pret: 32,30 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/placa-ornament-unica-pro-un-modul-aluminiu-319357>