

Furnizor: Sc Trivolt Distribution SRL Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, İlfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



SCHNEIDER PLACA ORNAMENT, UNICA PRO, UN MODUL, ANTRACIT

Schneider Electric New Unica cover frame NU411854 is in color anthracite The cover frame is made of polycarbonate, thermoplastic ABS-UV stabilised, making it as resistant as possible. This cover frame has 1 gang Besides, it reaches IKO4 protection level, which can help protect against impact. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. This cover frame is SVHC (substances of very high concern) free too. This cover frame belongs to Unica Pro aesthetic group. What's more, it well satisfied the standard of IEC 60669-1, IEC 60884-1. It is 227 mm in width. 85 mm in height. 10 mm in depth. Besides it is halogen free halogen free, which is good for your health. With 8 modules. The fixing mode of this device is clip-in. And the product weighs 0.036 kg. New Unica features innovative functions to carry the range into the smart homes of the future. Welcome to the new Unica a€" irresistible, beautiful, and innovative. Main

Range - New Unica

Device application - Mounting

Product or component type - Cover frame aesthetic name - Unica Pro

Number of gangs - 1 gang Installation direction - Horizontal

Type of frame - Single Number of modules - 8 modules

Fixing mode - Clip-in Colour tint - Anthracite (RAL 7021)

Complementary

Material - Thermoplastic ABS-UV stabilised: cover frame

Polycarbonate: intermediate plate Standards - IEC 60669-1

IEC 60884-1

Width - 227 mm

Height - 85 mm Depth - 10 mm

Net weight - 0.036 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK04

IP degree of protection - IP21D

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1 Package 1 Height - 8.5 cm

Package 1 Width - 22.7 cm

Package 1 Length - 1 cm Package 1 Weight - 42 g

Unit Type of Package 2 - BB1

Number of Units in Package 2 - 5

Package 2 Height - 5.5 cm Package 2 Width - 11 cm

Package 2 Length - 24.5 cm Package 2 Weight - 264 g Unit Type of Package 3 - S01

Number of Units in Package 3 - 10

Package 3 Height - 15 cm

Package 3 Width - 15 cm Package 3 Length - 40 cm

Package 3 Weight - 736 g

Pret: 41,98 lei (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/placa-ornament-unica-pro-un-modulantracit-319361