

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **SCHNEIDER PLACA ORNAMENT, UNICA PURE, UN MODUL, ALB**

Schneider Electric New Unica cover frame NU600289 is in color white Being made of plexiglass, polycarbonate material, this cover frame is quite reliable and resistant. This cover frame has 1 gang Besides, it reaches IK01 protection level, which can help protect against impact. Also, it is environment-friendly, with UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid reached. This cover frame is SVHC (substances of very high concern) free too. This cover frame belongs to Unica Pure aesthetic group. What's more, it well satisfied the standard of IEC 60669-1, IEC 60884-1. It is 85 mm in width. 90 mm in height. 11 mm in depth. Besides it is halogen free halogen free, which is good for your health. With 1 x 2 modules. The fixing mode of this device is clip-in. And the product weighs 0.03 kg. New Unica features innovative functions to carry the range into the smart homes of the future. Welcome to the new Unica æ" irresistible, beautiful, and innovative. Main

Range - New Unica

Device application - Mounting

Product or component type - Cover frame

aesthetic name - Unica Pure

Number of gangs - 1 gang

Installation direction - Horizontal

Type of frame - Single

Number of modules - 2 modules

Fixing mode - Clip-in

Colour tint - White

side color - White (RAL 9003)

Complementary

Material - Polycarbonate: intermediate plate

Plexiglass: cover frame

Standards - IEC 60884-1

IEC 60669-1

Width - 85 mm

Height - 90 mm

Depth - 11 mm

Net weight - 0.03 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK01

IP degree of protection - IP21D

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 2.7 cm

Package 1 Width - 9.7 cm

Package 1 Length - 13.0 cm

Package 1 Weight - 62.0 g

Unit Type of Package 2 - S03

Number of Units in Package 2 - 45

Package 2 Height - 30.0 cm

Package 2 Width - 30.0 cm

Package 2 Length - 40.0 cm

Package 2 Weight - 3.255 kg

Pret: 103,43 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/placa-ornament-unica-pure-un-modul-alb-319369>