

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **SCHNEIDER PLACA ORNAMENT, UNICA PURE, TREI MODULE, ALUMINIU**

Schneider Electric New Unica cover frame NU600680 is in color aluminium. The cover frame is made of polycarbonate, zamak, making it as resistant as possible. This cover frame has 3 gangs. Besides, it reaches IK04 protection level, which can help protect against impact. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. This cover frame is SVHC (substances of very high concern) free too. This cover frame belongs to Unica Pure aesthetic group. What's more, it well satisfied the standard of IEC 60669-1, IEC 60884-1. It is 226 mm in width. 90 mm in height. 11 mm in depth. Besides it is halogen free, which is good for your health. With 3 x 2 modules. The fixing mode of this device is clip-in. And the product weighs 0.233 kg. New Unica features innovative functions to carry the range into the smart homes of the future. Welcome to the new Unica æ" irresistible, beautiful, and innovative. Main

Range - New Unica

Device application - Mounting

Product or component type - Cover frame

aesthetic name - Unica Pure

Number of gangs - 3 gangs

Installation direction - Horizontal

Type of frame - Triple

Number of modules - 3 x 2 modules

Fixing mode - Clip-in

Colour tint - Aluminium

side color - White (RAL 9003)

Complementary

Material - Zamak: cover frame

Polycarbonate: intermediate plate

Standards - IEC 60669-1

IEC 60884-1

Width - 226 mm

Height - 90 mm

Depth - 11 mm

Net weight - 0.233 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK04

IP degree of protection - IP21D

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 2.5 cm

Package 1 Width - 9.5 cm

Package 1 Length - 26.5 cm

Package 1 Weight - 270 g

Unit Type of Package 2 - S03

Number of Units in Package 2 - 22

Package 2 Height - 30 cm

Package 2 Width - 30 cm

Package 2 Length - 40 cm

Package 2 Weight - 6.863 kg

Unit Type of Package 3 - P06

Number of Units in Package 3 - 176

Package 3 Height - 80 cm

Package 3 Width - 80 cm

Package 3 Length - 60 cm

Package 3 Weight - 59.916 kg

Pret: 279,23 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/placa-ornament-unica-pure-trei-module-aluminiu-319381>