

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER PLACA ORNAMENT, UNICA PRO, UN MODUL, ALB

This 1-gang New Unica cover frame is in color white with 1 x 2 modules. Being made of polycarbonate, thermoplastic ABS-UV stabilized material, this cover frame is quite reliable and resistant. It features protective painted surface treatment. This cover frame belongs to Unica Pro group. Simple and effective to install, mounting and fitting the cover frame to the device. It well satisfied the standard of IEC 60669-1, IEC 60884-1. It is 85 mm in width, 85 mm in height 10 mm in depth. The fixing mode of this device is clip-in. The IP rating of this device is IP21D which is very high. Besides, it reaches IK04 protection level, which can help protect against impact. This cover frame is SVHC (substances of very high concern) free. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Device application - Mounting

Product or component type - Cover frame

aesthetic name - Unica Pro

Number of gangs - 1 gang

Installation direction - Horizontal/vertical

Type of frame - Single

Number of modules - 2 modules

Fixing mode - Clip-in

Colour tint - White (RAL 9003)

Complementary

Material - Thermoplastic ABS-UV stabilised: cover frame

Polycarbonate: intermediate plate

Quantity per set - Set of 100

Standards - IEC 60669-1

IEC 60884-1

Width - 85 mm

Height - 85 mm

Depth - 10 mm

Net weight - 0.018 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK04

IP degree of protection - IP21D

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 1.0 cm

Package 1 Width - 8.5 cm

Package 1 Length - 8.5 cm

Package 1 Weight - 170.0 g

Pret: 455,96 lei (TVA inclus)

Detalii online: <https://www.materialeelectric.ro/placa-ornament-unica-pro-un-modul-alb-319393>