

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER PLACA ORNAMENT, UNICA STUDIO METAL, DOUA MODULE, ANTRACIT

Schneider Electric New Unica cover frame NU280453 is in color dark aluminium Being made of polycarbonate, thermoplastic ABS-UV stabilised material, this cover frame is quite reliable and resistant. This cover frame has 2 gangs Besides, it reaches IK04 protection level, which can help protect against impact. Also, it is environment-friendly, with UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid reached. This cover frame is SVHC (substances of very high concern) free too. This cover frame belongs to Unica Studio Metal aesthetic group. What's more, it well satisfied the standard of IEC 60669-1, IEC 60884-1. It is 156 mm in width. 85 mm in height. 10 mm in depth. Besides it is halogen free halogen free, which is good for your health. With 2 x 2 modules. The fixing mode of this device is clip-in. And the product weighs 0.033 kg. New Unica features innovative functions to carry the range into the smart homes of the future. Welcome to the new Unica æ" irresistible, beautiful, and innovative. Main

Range - New Unica
Device application - Mounting
Product or component type - Cover frame
aesthetic name - Unica Studio Metal
Number of gangs - 2 gangs
Installation direction - Horizontal/vertical
Type of frame - Double
Number of modules - 2 x 2 modules
Fixing mode - Screws
Colour tint - Dark aluminium
side color - Black (RAL 7021)
Complementary
Material - Polycarbonate: intermediate plate
Surface finish - Brushed finish
Quantity per set - Set of 3
Standards - IEC 60669-1
IEC 60884-1
Width - 156 mm
Height - 85 mm
Depth - 10 mm
Net weight - 0.033 kg
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
IK degree of protection - IK04
IP degree of protection - IP21D
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 1.0 cm
Package 1 Width - 8.5 cm
Package 1 Length - 15.6 cm
Package 1 Weight - 36.0 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 3
Package 2 Height - 6.8 cm
Package 2 Width - 12.8 cm
Package 2 Length - 18.8 cm
Package 2 Weight - 166 g
Unit Type of Package 3 - S04
Number of Units in Package 3 - 108
Package 3 Height - 30 cm
Package 3 Width - 40 cm
Package 3 Length - 60 cm
Package 3 Weight - 6.724 kg
Pret: 77,03 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/placa-ornament-unica-studio-metal-doua-module-antracit-319511>