

Furnizor: Sc Trivolt Distribution SRL Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 ( primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, İlfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



## SCHNEIDER PLACA ORNAMENT, UNICA STUDIO METAL, PATRU **MODULE, ALUMINIU**

Schneider Electric New Unica cover frame NU280855 is in color white aluminium The cover frame is made of polycarbonate, thermoplastic ABS-UV stabilised, making it as resistant as possible. This cover frame has 4 gangs Besides, it reaches IK04 protection level, which can help protect against impact. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. This cover frame is SVHC (substances of very high concern) free too. This cover frame belongs to Unica Studio Metal aesthetic group. What's more, it well satisfied the standard of IEC 60669-1, IEC 60884-1. It is 298 mm in width. 85 mm in height. 10 mm in depth. Besides it is halogen free halogen free, which is good for your health. With  $4 \times 2$  modules. The fixing mode of this device is clip-in. And the product weighs 0.063 kg. New Unica features innovative functions to carry the range into the smart homes of the future. Welcome to the new Unica a€" irresistible, beautiful, and innovative.Main

Range - New Unica

Pange - New Unica
Device application - Mounting
Product or component type - Cover frame
aesthetic name - Unica Studio Metal
Number of gangs - 4 gangs
Installation direction - Horizontal/vertical
Type of frame - Quadruple

Number of modules - 4 x 2 modules

Fixing mode - Screws

Colour tint - White aluminium side color - White (RAL 9003)

Complementary

Material - Polycarbonate: intermediate plate Surface finish - Brushed finish Quantity per set - Second 3

Standards - IEC 60669-1 IEC 60884-1 Width - 298 mm Height - 85 mm

Depth - 10 mm

Net weight - 0.063 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK04 IP degree of protection - IP21D

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 1.0 cm Package 1 Width - 8.5 cm Package 1 Length - 30.0 cm Package 1 Weight - 64.0 g

Unit Type of Package 2 - BB1

Number of Units in Package 2 - 3
Package 2 Height - 7.5 cm
Package 2 Width - 9.5 cm
Package 2 Length - 32 cm

Package 2 Weight - 263 g Unit Type of Package 3 - S03

Number of Units in Package 3 - 27

Package 3 Height - 30 cm

Package 3 Width - 30 cm

Package 3 Length - 40 cm Package 3 Weight - 2.812 kg Pret: 154,04 lei (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/placa-ornament-unica-studio-metalpatru-module-aluminiu-319534