

Furnizor: Sc Trivolt Distribution SRL Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 ( primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



## SCHNEIDER PLACA ORNAMENT, UNICA STUDIO METAL, UN MODUL, **CUPRU**

Schneider Electric New Unica cover frame NU280257 is in color copper Being made of polycarbonate, thermoplastic ABS-UV stabilised material, this cover frame is quite reliable and resistant. This cover frame has 1 gang Besides, it reaches IKO4 protection level, which can help protect against impact. Also, it is environment-friendly, with UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid reached. This cover frame is SVHC (substances of very high concern) free too. This cover frame belongs to Unica Studio Metal aesthetic group. What's more, it well satisfied the standard of IEC 60669-1, IEC 60884-1. It is 85 mm in width. 85 mm in height. 10 mm in depth. Besides it is halogen free halogen free, which is good for your health. With 1 x 2 modules. The fixing mode of this device is clip-in. And the product weighs 0.02 kg. New Unica features innovative functions to carry the range into the smart homes of the future. Welcome to the new Unica a£" irresistible, beautiful, and innovative. Main

Range - New Unica

Product or component type - Cover frame aesthetic name - Unica Studio Metal

Number of gangs - 1 gang Installation direction - Horizontal/vertical

Type of frame - Single Number of modules - 2 modules

Fixing mode - Clip-in Colour tint - Copper

side color - White (RAL 9003)

Complementary

Material - Thermoplastic ABS-UV stabilised: cover frame

Polycarbonate: intermediate plate Surface finish - Dotted finish Standards - IEC 60669-1

IEC 60884-1 Width - 85 mm Height - 85 mm Depth - 10 mm Net weight - 0.02 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %) Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK04 IP degree of protection - IP21D

Packing Units

Unit Type of Package 1 - PCE Number of Units in Package 1 - 1

Package 1 Height - 1 cm Package 1 Width - 8.5 cm

Package 1 Length - 8.5 cm Package 1 Weight - 21.4 g Unit Type of Package 2 - BB1

Number of Units in Package 2 - 5 Package 2 Height - 10.5 cm Package 2 Width - 11 cm Package 2 Length - 12 cm Package 2 Weight - 164.5 g

Unit Type of Package 3 - S04

Number of Units in Package 3 - 150

Package 3 Height - 30 cm Package 3 Width - 40 cm Package 3 Length - 60 cm Package 3 Weight - 5.585 kg Pret: 0,00 lei (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/placa-ornament-unica-studio-metal-unmodul-cupru-319582