

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER NEW UNICA - STATIE DE LUCRU - INCASTRAT - 2 X 10 MODULE - ANTIBACTERIAN - ALB

Schneider Electric New Unica workstation NU171020 is in color white. It is 300 mm in width, 165 mm in height, 62 mm in depth. And the product weighs 0.594 kg. With 2 x 10 modules. Its fixing mode is claws, embedment. Its matching mounting box can be recessed into the surface of the wall with flush type. Being made of ABS (acrylonitrile butadiene-styrene), PC material, this workstation is quite reliable and resistant. Besides, it reaches IK04 protection level, which can help protect against impact. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. This workstation is SVHC (substances of very high concern) free too. This device is (compatible with) Unica. Besides it is halogen free halogen free, which is good for your health. The antibacterial surface treatment meets the requirements for places like restaurants or hospitals. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Workstation

Number of modules - 2 x 10 modules

Fixing mode - Claws

Embedment

Colour tint - White (RAL 9003)

Complementary

Provided equipment - Cover frame

Fixing frame

device mounting - Flush

Cable entry - 4 bottom cable entries 50 x 35 mm for size 25 mm for diameter

8 knock-outs 20 mm for diameter

8 knock-outs 25 mm for diameter

4 bottom cable entries 50 x 35 mm for size 20 mm for diameter

Fire resistance - 850 A°C, extinction time Material - ABS (acrylonitrile butadiene-styrene): separator

PC: box

ABS (acrylonitrile butadiene-styrene): cover frame

PC: tower

Surface treatment - Antibacterial

Depth - 62 mm

Width - 300 mm

Height - 165 mm

Net weight - 0.594 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK04

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 7.9 cm

Package 1 Width - 17.9 cm

Package 1 Length - 31.4 cm

Package 1 Weight - 776 g

Unit Type of Package 2 - S04

Number of Units in Package 2 - 10

Package 2 Height - 30 cm

Package 2 Width - 40 cm

Package 2 Length - 60 cm

Package 2 Weight - 7.76 kg

Unit Type of Package 3 - P06

Number of Units in Package 3 - 40

Package 3 Height - 77 cm

Package 3 Width - 80 cm

Package 3 Length - 60 cm

Package 3 Weight - 42.66 kg

Pret: 218,04 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/new-unica-statie-de-lucru-incastrat-2-x-10-module-antibacterian-alb-319723>