


Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140 Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, Ilfov Banca: BRD IBAN: RO34BRDE441SV13182234410



OBO BETERMANN FIRE PROTECTION DUCT 190/E30, INTERNAL HEIGHT 105 MM | TYPE BSKH 091016

The fibre glass light-duty concrete ducts, which can be flamed on four sides, can be mounted on OBO mounting systems, thus offering the greatest possible flexibility in cable routing in emergency and escape routes (installation duct to DIN 4102 Part 11) or in the maintenance of electrical function (to DIN 4102 Part 12). This allows elegant avoidance of objects from other areas such as heating, ventilation and sanitary applications. Mounting under the ceiling is simple, using U-shaped suspended supports and a bracket, or on a U transverse profile suspended with threaded rods. The OBO BSKH is simply attached loosely. Mounted connectors ensure quick mounting in situ, whilst loosely placed covers ensure quick inspection and reassignment. Type: BSKH 091016 Dimen-sion B (mm): 260 Dimen-sion H (mm): 175 Dimen-sion b (mm): 160 Dimen-sion h (mm): 105 Length (mm): 1000 Pack.m: 1 Weightkg/100 m: 1720,000 Item No.: 7215186 Pret: 0.00 lei (TVA inclus)