

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

Zeichnung / Drawing Belegung / Configuration Belegung nach TIA/EIA 568 A / Configuration to TIA/EIA 568 A Belegung nach TIA/EIA 568 B / Configuration to TIA/EIA 568 B	<u>SCHRACK SET 24 MODUL RJ45 ECRANAT,CLASAEA 10GB POE+,PERFORMANCE LINE</u> EAN-Code 9004840566451 Lungime 180,00mm Latime neta 75,00mm Inaltime 65,00mm Masa neta 0,74kg. Temperatura minima a mediului ambiant -40°C Temperatura maxima a mediului ambiant 70°C Produs Modul conector Ecranaj ecranat Format SCHRACK SFB Conector standard IEC 60603-7-51 Categorie Cat.6a/10GB Class E<sub>A</sub> acc. to ISO/IEC 11801 Amendment 1/2 typical link length > 2m, in combination with a CP-cable: CP-Link typ. > 10m 10GbE is supported PoE+ Da Cicluri de conectare %¥ 750 Insertion force %¤ 30N Conductor diameter solid 0,51-0,65mmAWG24/1 - AWG 22/1 Insulation diameter 5 - 9mm Reusable (Module) %¤ 5 cycles with the same diameter RoHS Conform cu directiva EU 2002/95/EC Housing Zinc diecast Strain-relief sliver Zinc diecast Surface nickel plated Shield spring Stainless steel PCB FR4 PCB finish HAL lead-free Material contacte Spring steel Contact finish 0,762 µm / 30 µin Au Insulation housing PA black (RAL9005) Contact support plate PC yellow (RAL1021) Dust protection cover PC clear IDC CuNi2Si IDC finish min. 3-6 µm (120-240µin) Sn Particularte ingress IP2X Water ingress IPX0 Impachetare Bio-degradable Contact resistance %¤ 20m„! Rezistenta izolatii %¥ 500 M„! Votage proof - contact-contac %¥ 1000 (DC)V Current carring capacity at 50°C 1,25A Transfer Impedance @ 1 MHz = %¤ 100m„!@ 10 MHz = %¤ 200m„!@ 80 MHz = %¤ 1600m„! Porturi 1 Pret: 521,52 lei (TVA inclus) Detalii online: https://www.materialeelectrice.ro/set-24-modul-rj45-ecranat-clasaea-10gb-poe-performance-line-84733
--	---