

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER EASY UPS 3M 160KVA 400V 3:3 UPS FOR EXTERNAL BATTERIES, START-UP 5X8

Descriere Easy-to-install, easy-to-connect, easy-to-use, and easy-to-service 160 kVA 3 phase UPS with advanced product features, robust electrical specifications and compact design making your business continuity easy. Ideal for small and medium data centers and other business critical applications, this UPS is EcoStruxure-ready to give you peace of mind with cloud-based remote monitoring and management. It is supplied without batteries, so you can easily customize your battery solution. Includes 5x8 start-up service.

Denumire model Easy UPS 3M 160kVA 400V 3:3 UPS for external batteries, Start-up 5x8
Include Filtru de praf , Ghid de instalare , Serviciu de pornire

Capacitate putere de iesire 160.0 KW / 160.0 kVA

Putere max. configurabila (wati) 160.0 KW / 160.0 kVA

Tensiune nominala la iesire 400 3 Faz

Distorsiune tensiune de iesire Sub 3%

Frecventa de iesire (sincronizata cu alimentarea de la retea) 50 Hz , 60 Hz

Alte tensiuni de iesire 380, 415V

Online cu dubla conversie

Tip forma de unda Unda sinusoidala

Toleranta tensiune de iesire +/-1%

Tensiune de iesire THD < 3% sarcina liniara si < 5% sarcina neliniara

Functionare la suprasarcina 150% for 1 minute 125% for 10 minutes

Tensiune nominala de intrare 400 3 Faz

Frecventa de intrare 40 - 70 Hz

Interval tensiune de intrare pentru operatii principale 342 - 477 V

Alte tensiuni la intrare 380 , 415

Curent maxim de intrare 262 A

Rezistenta maxima la scurtcircuit (Icw) 10.0

Distorsiune armonica totala de intrare Sub 3% pentru capacitate maxima

Tip de acumulator Fara baterie interna - utilizeaza sistemul de baterie extern

Port(uri) interfata E3M_ColdStart , E3M_parallel

Panou de cda Interfata utilizator cu ecran tactil LCD

Alarma sonora Alarmer sonore si vizibile prioritizate dupa gravitate

Inaltime maxima 1300.0 mm

Latime maxima 500.0 mm

Adancime maxima 850.0 mm

Greutate neta 227.0 kg

Greutate de transport 257.0 kg

Inaltime transport 1500.0 mm

Latime de transport 625.0 mm

Adancime transport 975.0 mm

Culoare RAL 9003

Mediu de operare 0 - 40 °C

Umiditate relativa de functionare 0 - 95 (non-condensing) %

Inaltime de operare 0-1476.3 metri

Temperatura de depozitare -25 to 55 °C

Umiditate relativa depozitare 0 - 95 (non-condensing) %

Inaltime depozitare 0-15000 metri

Zgomot sonor la 1 metru de suprafata unitatii 72.000 dB

Pierdere termica online 27297.000 BTU/h

Clasa de protectie IP 20

Aprobari reglementare EN/IEC 62040-1 , IEC 62040-2 , IEC 62040-3 , IEC 62040-4

Garantie standard 1 an reparatii sau inlocuire pe loc cu pornire autorizata din fabrica

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/easy-ups-3m-160kva-400v-3-3-ups-for-external-batteries-start-up-5x8-98131>