

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER APC PARALLEL MAINTENANCE BYPASS FOR 2 UPS (1+1) 3:1 15-20KVA WALLMOUNT

APC SBPAR3I15K20R2M2-WP

Denumire model APC Parallel Maintenance Bypass for 2 UPS (1+1) 3:1 15-20kVA
Wallmount

Include Installation guide

Timp de livrare standard Usually Ships within 4 Weeks

, United Arab Emirates , Afghanistan , , , , , Azerbaijan , And Herzegovina , , Belgium , ,
, , , , Darussalam , , , , , THE DEMOCRATIC REPUBLIC OF THE , Central African
Republic , , Switzerland , Cote D'Ivoire , Cook Islands , Cameroon , , Serbia And
Montenegro , Cyprus , Czech Republic , Germany , , Denmark , , Egypt , Western
Sahara , Spain , Ethiopia , Finland , , France , , United Kingdom , , French Guiana , , , ,
Guinea , Guadeloupe , Equatol Guinea , Greece , , Hungary , Indonesia , Ireland , , ,
Iraq , Iran (Islamic Republic Of) , Iceland , Italy , Jordan , , Cambodia , KOREA,
REPUBLIC OF , Kuwait , Kazakhstan , Lebanon , , , , Lithuania , Luxembourg , Latvia ,
Morocco , Moldova , Republic Of , , , , Myanmar , Martinique , , , , Malaysia ,
Mozambique , , , Netherlands , Norway , , New Zealand , , Papua New Guinea ,
Philippines , , Poland , Portugal , Reunion , , Russian Federation , , Saudi Arabia , ,
Sweden , , , Slovakia (Slovak Republic) , , , , Turks And Caicos Islands , Chad , , Thailand
, , , East Timor , Turkey , , TANZANIA , UNITED REPUBLIC OF , Ukraine , , , Viet Nam , ,
, South Africa , ,

Tensiune nominala la iesire 220V

Conexiuni de iesire (1) Hard Wire 3-wire (H N + G) (Battery Backup)

Tensiune nominala de intrare 400V 3PH

Greutate neta 100 kg

Inaltime maxima 1200 mm

Latime maxima 1010 mm

Adancime maxima 800 mm

Greutate de transport 120 kg

Inaltime transport 1600 mm

Latime de transport 1200 mm

Adancime transport 800 mm

Mediu de operare 0 - 40 °C

Umiditate relativa de functionare 0 - 95 %

Inaltime de operare 0-3000 meters

Temperatura de depozitare -15 - 45 °C

Umiditate relativa depozitare 0 - 95 %

Inaltime depozitare 0-9000 meters

Aprobari reglementare EN 50091-2 , EN/IEC 62040-1-1 , EN/IEC 62040-3 , VFI-SS-111

Garantie standard 1 year repair or replace

Pret: 0,00 lei (TVA inclus)

Detalii online: [https://www.materialeelectric.ro/apc-parallel-maintenance-bypass-for-2-
ups-1-1-3-1-15-20kva-wallmount-98444](https://www.materialeelectric.ro/apc-parallel-maintenance-bypass-for-2-
ups-1-1-3-1-15-20kva-wallmount-98444)