


# SCHNEIDER ION7650 - WDISPL - 5MB 512S - 5A 240VAC/300VDC 50HZ - RS+T2+E - 8I+3R+4O

gama PowerLogic
nume produs PowerLogic ION7650
nume scurt al dispozitivului ION7650
tip produs sau componenta Energy and power quality meter
power quality analysis harmonic distortion - compliance monitoring - dip and swell, transient - disturbance direction detection - programmablity (logic and math functions) - setpoint learning - voltage sag and swell detection - waveform capture - up to the 63rd harmonic - conformitate cu IEC 61000-4-30 class A power quality measurement - conformitate cu EN 50160 compliance report
domeniul de aplicare al aparatului Energy pulsing and totalisation - Co-generation and IPP monitoring - Load curtailment - Tariff metering - Demand and power factor control - Instrument transformer correction - Equipment monitoring and control
tip de masurare Factor de putere total - Factor de putere per phase - Apparent power total - Apparent power per phase - Putere activa total - Putere activa per phase - Reactive power total - Reactive power per phase - Curent - Tensiune - Frecventa
supply voltage 110...300 V c.c. - 85...240 V c.a. 47...63 Hz
frecventa retea 50 Hz
[In] curent nominal 5 A
descriere poli 3P - 3P + N - 1P + N
puterea consumata in VA 20 VA
maximum power consumption in VA 45 VA
rezolutie afisaj 320 x 240 pixeli QVGA
tip afisaj LCD retro-iluminat
sampling rate 512 samples/cycle
curentul de masura 0…5 A
input type curent 0.005...20 A 0.002 Ohm)
masurarea tensiunii 100…600 V c.a. faza la faza - 57…347 V c.a. faza la neutru

gama de masurare a frecventei 42…69 Hz
numar de intrari 8 digital 120 V c.c.
precizie de masurare Curent 0.1 % 1...5 A - Tensiune 0.1 % 57...288 V - Energie 0.2 %
clasa de precizie Class 0.2S energie conformitate cu IEC 62053-22
numar de iesiri 3 releu - 4 cu semiconductori
protocol port de comunicare ION - Telnet - IEC 61850 - DNP3 - Modbus - TCP/IP
suport pentru port de comunicatie SUB-D 9 RS232 - ST fibre optice - RJ11 modem - RJ45 Ethernet - RS485
Inregistrare data Jurnale de evenimente - Evaluare a tendintei/prognoza - Marcaj temporal - GPS synchronisation - Ordine deinregistrare a evenimentelor - Min/max al valorilor instantanee - Jurnale de date
rata de transmisie 300...115200 bauds - 10/100 Mbit/s - 300...57600 bauds - compatibilitate electromagnetica Descarcare electrostatica conformitate cu IEC 61000-4-2 - Sensibilitate la campuri electromagnetice conformitate cu IEC 61000-4-3 - Tranzienti rapizi/test de imunitate la impulsuri de ionizare conformitate cu IEC 61000-4-4 - 1.2/50 µs test de imunitate la unda de soc conformitate cu IEC 61000-4-5 - Emisii conduse si radiateB conformitate cu CISPR 22
mod de montare Montajincastrat
suport de montare Usa carcasa
tip de instalare Instalarein interior
categorie de supratensiune III
grad de protectie IP Spate IP30 conformitate cu SR EN 60529 - Fata frontala IP50 conformitate cu SR EN 60529
umiditate relativa 5…95 %
grad de poluare 2
temperatura de utilizare -20…70 °C
temperatura de depozitare -40…85 °C
altitudine de functionare 0...2000 m
standarde IEC 61010-1
latime 192 mm
adancime 174 mm
inaltime 192 mm
greutate produs 1,9 kg
Garantie 18 luni
Pret: 40.181,58 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/ion7650-wdispl-5mb-512s-5a-240vac-300vdc-50hz-rs-t2-e-8i-3r-4o-100030