

SCHNEIDER MODUL PROCESOR M580 - NIVEL 2 - LA DISTANTA

gama de produse Modicon M580
tip produs sau componenta Modul procesor
numar de rackuri 4
Local I/O processor capacity (discrete) 2048 I/O
Local I/O processor capacity (analog) 512 I/O
Number of application specific channel (local rack) 72
intrare/iesire specifica aplicatiei Legatura sela - Contor - Marcare temporala precisa - HART - Control miscare - Encoder SSI
verificari Control de proces
canale de control Bucle programabile
tip de conexiune integrata 1 Ethernet TCP/IP pentru service port - 2 Ethernet TCP/IP pentru device network - USB type mini B
numar de statii I/O la distanta 8 - 2 pe remote drop
numar echipamente distribuite 64
procesorul modulului de comunicatie 2 Modul de comunicatie Ethernet - 8 Modul interfata AS
serviciu de comunicare Scanner DIO - RIO scanner
descriere memorie Extensibil flash, 4 GB pentru stocare date - Integrat RAM, 10 kB pentru Memorie - Integrat RAM, 8 MB pentru program process - Integrat RAM, 768 kB pentru data process - Integrat RAM, 2 MB pentru program safety - Integrat RAM, 512 kB pentru data safety
structura aplicatie 64 operatii pentru evenimente - 2 sarcini auxiliare - 1 operatie principala ciclica/periodica - 1 operatie rapida periodica
numar de instructiuni pe ms 7.5 Kinst/ms 65 % Boolean + 35 % aritmetica fixa - 10 Kinst/ms 100 % Boolean
consum de curent 295 mA la 24 V c.c.
siguranta MTBF 600000 H
marcaj CE
rezistenta la vibratii 3 gn
rezistenta la socuri 15 gn

temperatura ambianta pentru utilizare 0…60 °C
temperatura de depozitare -40…85 °C
altitudinea de functionare 0...2000 m - 2000...5000 m cu
umiditate relativa 5…95 % la 55 °C fara condensare
grad de protectie IP IP20
directivele 2014/35/EU - directiva joasa tensiune - 2014/30/EU - compatibilitate electromagnetica - 2012/19/EU - WEEE directive
standarde EN 61131-2 - EN 61000-6-4 - EN 61000-6-2 - EN 61010-2-201
certificari produs EAC - Certificare navala - UL - CE - CSA - RCM
alimentare Alimentare electrica interna prin rastel
LED de stare Functionare procesor (RUN) 1 LED (verde) - Defect procesor sau sistem(ERR) 1 LED (rosu) - Defect modul I/O (I/O) 1 LED (rosu) - Descarcare in curs 1 LED (verde) - Card memorie sau eroare flash CPU (rezerva) 1 LED (rosu) - ETH MS (Status configurare port Ethernet) 1 LED (green/red) - Eth NS (Status retea Ethernet) 1 LED (green/red) - Processor in safety mode (SRUN) 1 LED (verde) - Processor in maintenance mode (SMOD) 1 LED (verde) - I/O values overrided by user (FORCED IO) 1 LED (rosu)
greutate produs 0,849 kg
Stare oferta sustenabila Produs Green Premium
Regulamentul REACH Declaratia REACH
Directiva RoHS UE Conformitate proactiva (Produs in afara domeniului de aplicare a EU RoHS) Declaratia RoHS UE
Fara mercur Da
Informatii privind scutirea de la RoHS Da
Regulamentul RoHS Declaratia RoHS
Profil circularitate Informatii privind sfarsitul duratei de viata
WEEE In Uniunea Europeana, produsele trebuie reciclate respectand sistemul specific de colectare a deseurilor si nu trebuie sa ajunga in pubelele de colectare a deseurilor menajere.
Garantie 18 luni
Pret: 16.930,61 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/modul-procesor-m580-nivel-2-la-distanta-100840