



Capacitate disjunctor alimentare 35 A

Tip de acumulator VRLA
Module baterie incluse 4
Timp de reincarcare tipic 5 ora(ore)
Replacement Battery SYBT4
Cantitate RBC™ 4
Port(uri) interfata DB-9 RS-232 , Smart-Slot
Carduri SmartSlot™ preinstalate AP9619
Panou de cda Consola de cda si stare LCD multifunctional
Alarma sonora Alarme sonore si vizibile prioritizate dupa gravitate
Intrerupere de urgenta a alimentarii (EPO) Yes
Inaltime maxima 1499.0 mm
Latime maxima 559.0 mm
Adancime maxima 813.0 mm
Greutate neta 599.1 kg
Greutate de transport 630.0 kg
Inaltime transport 1643.0 mm
Latime de transport 650.0 mm
Adancime transport 1062.0 mm
Culoare Negru
Unitati per palet 1.0
Mediu de operare 0 - 40 °C
Umiditate relativa de functionare 0 - 95 %
Inaltime de operare 0-999.9 metri
Temperatura de depozitare -50 - 40 °C
Umiditate relativa depozitare 0 - 95 %
Inaltime depozitare 0-15000 metri
Zgomot sonor la 1 metru de suprafata unitatii 64.000 dB
Pierdere termica online 2170.000 BTU/h
Clasa de protectie IP 20
Aprobari reglementare C-tick , CE , EN 50091-2 , EN/IEC 62040-3 , IEC 61000-3-2 , IEC 61000-3-3 , ISO 14001 , ISO 9001 , VFI-SS-112
Garantie standard 1 an reparatii sau inlocuire
Pret: 0,00 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/apc-smart-ups-vt-15kva-400v-w-4-batt-modules-start-up-5x8-internal-maintenance-bypass-102430>