SCHNEIDER CONTROLER MOTOR LTM R TESYS T - 24 V C.C. 8 A PENTRU DEVICENET

gama TeSys
nume produs TeSys T
nume scurt al dispozitivului LTMR
tip produs sau componenta Controler motor
domeniul de aplicare al aparatului Equipment monitoring and control
curentul de masura 0,4…8 A
[Us] tensiune nominala de alimentare 24 V c.c.
curentul consumat 56...127 mA
limitele tensiunii de alimentare 20,4…26,24 V c.c.
protocol port de comunicare DeviceNet
tip magistrala DeviceNet ISO 1198 interfata, adresare 1...64, rata de transmisie 125...500 kbit/s, cutie de borne cu 4 twisted shielded pairs cable
[Ui] tensiune nominala de izolatie 690 V conformitate cu EN/IEC 60947-1 - 690 V conformitate cu CSA C22.2 No 15 - 690 V conformitate cu UL 508
[Uimp] tensiune de tinere la impuls 6 kV current or voltage measurement circuit conformitate cu EN/IEC 60947-4-1 - 0,8 kV communication circuit conformitate cu EN/IEC 60947-4-1 - 0,8 kV supply, inputs and outputs conformitate cu EN/IEC 60947-4-1
incercare la scurtcircuit 100 kA conformitate cu EN/IEC 60947-4-1
calibrul fuzibilului asociat 4 A gG pentru iesire - 0,5 A gG pentru circuit de cda
tip de protectie Protectie la suprasarcina termica - Overload - Power factor vation - Protectie fata de polaritate inversa - Protectie de scurgere la pamant - Protectie termica - Overload (long time) - Defect faza - Load fluctuation - Phase unbalance - Locked rotor
network and machine diagnosis type Fault recording - Waiting time after overload tripping - Remaining operating time before overload tripping - Phase fault and earth fault trip counters - Starting current and time - Trip history information - Trip context information - Motor control command recording - Running hours counter/operating time - Event recording

numar de intrare logica 6
curent de intrare 7 mA
stare curenta 0 garantata Logic input < 5 V si 0.1 A) - 1 % tensiune (100...830 V) - 3 % factor de putere (cos ? > 0.6) - 5 % earth fault current external measurement (< 5 % or 0.01 A) - +/- 30 min/year internal clock - 0,02 temperature - 1 % curent - 5 % active and reactive power
categorie de supratensiune III
pasul conexiunii 5,08 mm
conexiuni - borne Circuit de cda conector 1 cablu(ri) 0,25…2,5 mm² (AWG 24 - AWG 14)flexibil cu - Circuit de cda conector 1 cablu(ri) 0,2…2,5 mm² (AWG 24 - AWG 14)flexibil fara - Circuit de cda conector 1 cablu(ri) 0,25…2,5 mm² (AWG 24 - AWG 14)flexibil fara - Circuit de cda conector 1 cablu(ri) 0,2…2,5 mm² (AWG 24 - AWG 14)solid fara - Circuit de cda conector 2 cablu(ri) 0,2…1 mm² (AWG 24 - AWG 14)flexibil cu - Circuit de cda conector 2 cablu(ri) 0,2…1,5 mm² (AWG 24 - AWG 14)flexibil fara - Circuit de cda conector 2 cablu(ri) 0,5…1,5 mm² (AWG 24 - AWG 14)flexibil fara - Circuit de cda conector 2 cablu(ri) 0,2…1 mm² (AWG 24 - AWG 14)solid fara
cuplu de strangere Circuit de cda 0,5…0,6 N.m plat surubelnita 3 mm
grad de poluare 3
compatibilitate electromagnetica Descarcare electrostatica, 3 (8 kV air, 6 kV contact) (EN/IEC 61000-4-2) - Campuri RF radiate, 3 (10 V/m) (EN/IEC 61000-4-3) - Test de imunitate la tranzienti rapizi, nivel 3 (2 kV) (EN/IEC 61000-4-4) - Test de imunitate la tranzienti rapizi, level 4 (4 kV) (EN/IEC 61000-4-4) - Test de imunitate la caderi de tensiune si intreruperi (70 %, 500 ms) (EN/IEC 61000-4-11) - Perturba?ii conduse de RF (10 V) (EN/IEC 61000-4-6) - Supratensiuni tranzitorii (0.5 kV) (EN/IEC 61000-4-5) - Supratensiuni tranzitorii (1 kV) (EN/IEC 61000-4-5) - Supratensiuni tranzitorii (1 kV) (EN/IEC 61000-4-5) - Supratensiuni tranzitorii (1 kV) (EN/IEC 61000-4-5) - Supratensiuni tranzitorii (2 kV) (EN/IEC 61000-4-5) - Supratensiuni tranzitorii (2 kV) (EN/IEC 61000-4-5) - Supratensiuni tranzitorii (4 kV) (EN/IEC 61000-4-5)
latime 91 mm
inaltime 61 mm
adancime 122,5 mm
greutate produs 0,53 kg
servicii Web Server web
Cod compatibilitate LTMR
standarde SR EN 60947-4-1 - CSA C22.2 No 15 - UL 508 - IACS E10 - IEC 60947-4-1
certificari produs LROS (Lloyds register of shipping) - DNV - GL - UL - C-Tick - BV - CSA - ATEX - RINA - KERI - CCC - ABS - EAC - RMRoS - NOM
tratament protector 12 x 24 hour cycles conformitate cu EN/IEC 60068-2-30 - 48 h conformitate cu EN/IEC 60070-2-11 - TH conformitate cu EN/IEC 60068
rezistenta la foc 650 °C conformitate cu EN/IEC 60695-2-12 - 960 °C conformitate cu UL 94
temperatura de utilizare -20…60 °C
temperatura de depozitare -40…80 °C
altitudinea de functionare Stare oferta sustenabila Produs Green Premium
Regulamentul REACH Declaratia REACH
Directiva RoHS UE Under investigation
Fara mercur Da
Informatii privind scutirea de la RoHS Da
Regulamentul RoHS Declaratia RoHS Produs in afara domeniului de aplicare a RoHS . Declaratia privind substantele in scop informativ.
Raport de mediu Profilul ambiental al produsului
Profil circularitate Informatii privind sfarsitul duratei de viata
WEEE In Uniunea Europeana, produsele trebuie reciclate respectand sistemul specific de colectare a deseurilor si nu trebuie sa ajunga in pubelele de colectare a deseurilor menajere.
Garantie 18 luni
Pret: 2.941,62 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/controler-motor-ltm-r-tesys-t-24-v-c-c-8-a-pentru-devicenet-103815