



CAVI CABLU NHXH CU INTARZIERE LA FOC, FARA HALOGENURI 3X10

Cablu din cupru cu izolatie rezistenta la foc, fara halogenuri (Halogen Free) .

Caracteristici :

Emisie redusa de fum, fara gaze otravitoare

Bazat pe standarde: VDE 0276-604/VDE 0266 HD 604 S1

Rezistenta la foc 180 minute . Rezistenta in flacara 90 minute.

Temperatura de lucra -40°C.....+ 90°C

Tensiune 0,6-1KV

| | |
|------------------------------|--|
| 1. FLAME RETARDANT | IEC 60332-1-2;VDE 0482-332-1-2 EN 60332-1-2/BS EN 60332-1-2 |
| 2. FLAME PROPAGATION | IEC 60332-3-24/ VDE 0482-332-3-24 EN 60332 -3-24 BS EN 60332-3-24 |
| 3. SMOKE DENSITY | IEC 61034-2 VDE 0482-267-2-3 EN 61034-2/BS-EN 61034-2 |
| 4. CORROSIVE GAS TEST | IEC 60754-2;VDE 0482-267-2-3 EN 50267-2-3/BS EN 50267-2-3 |
| 5. HALOGEN-FREE TEST | IEC 60754-1;VDE 0482-267-2-1 EN 50267-2-1/BS EN 50267-2-1 |
| 6. CIRCUIT INTEGRITY(FE 180) | IEC 60331-21 |

7. CIRCUIT INTEGRITY WITH SHOCK IEC 6033-31/EN 50363 BS EN 50362 /VDE 0482-362

8. SYSTEM CIRCUIT INTEGRITY DIN 4102-12(E90)

Pret: 39,52 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/cablu-nhxx-cu-intarziere-la-foc-fara-halogenuri-3x10-11231>