www.MATERIALE ELECTRICE.ro
Consiliere specializata



LOVATO SURGE PROTECTION DEVICE TYPE 1 AND 2 WITH PLUG-IN CARTRIDGE, IEC IMPULSE CURRENT IIMP (10/350?S) 12.5KA PER POLE, 1P+N. CU CONTACT COMANDA DE LA DISTANTA

Cod producator Lovato: Surge Protection Device (SPD)
Tip produs: SA0
Operating voltage type: AC
Application: AC Power lines
Numar de poli: 1P+N
Number of DIN modules: 2
Relay output: Da
SPD according to IEC/EN 61643-11: Da
Rated operational voltage AC (IEC): VAC 230
Maximum continuous voltage (IEC) Uc: V 320
Impulse current (IEC) Iimp 10/350 (L-N/N-PE): kA 12.5 / 50
Maximum discharge current (IEC) Imax 8/20 (L-N/N-PE): kA 60 / 50
Rated discharge current (IEC) In 8/20 (L-N/N-PE): kA 25 / 30
Voltage protection level (IEC) Up (L-N/N-PE):
Temporary overvoltage (TOV) resistance Ut (L-N for 5s): V 335
Residual voltage (IEC) Ures (L-N/N-PE) at 5kA (8/20): kV 0.8 / 0.2
Follow current (IEC) If (N-PE) rms: A >100
Tripping time ta (L-N/N-PE): ns
Thermal isolation protection: Da
Backup protection fuse (IEC) with supply fuse >160A (L-N/N-PE): 160 Gg
Maximum short circuit current (IEC) at 50Hz: kA 25
Status indicator - operating / end of life: Frontal indication/Aux contact
Max altitude: m 2000
Mounting: Din rail
Tightening torque for terminals max: Nm 3

Conductor section - Flexible max (IEC): mm² 25
Conductor section - Rigid max (IEC): mm² 35
Greutate: g 365
Frontal IP degree: IP20
Type of contact: CO
Tightening torque for terminals max: Nm 0.25
Conductor section max (IEC): mm² 1.5
Pret: 1.779,74 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/surge-protection-device-type-1-and-2-with-plug-in-cartridge-iec-impulse-current-iimp-10-350ms-12-5ka-per-pole-1p-n-cu-contact-comanda-de-la-distanta-126742