www.MATERIALE ELECTRICE.ro
Consiliere specializata



LOVATO DESCARCATOR TIP 1 SI 2 MODNOBLOC, IEC IMPULSE CURRENT IIMP (10/350?S) 12.5KA PER POLE, 4P. CU CONTACT COMANDA DE LA DISTANTA

Cod producator Lovato: Surge Protection Device (SPD)
Tip produs: SA0B
Operating voltage type: AC
Application: AC Power lines
Numar de poli: 4P
Number of DIN modules: 4
Relay output: Da
SPD according to IEC/EN 61643-11: Da
Rated operational voltage AC (IEC): VAC 230 / 400
Maximum continuous voltage (IEC) Uc: V 320
Impulse current (IEC) Iimp 10/350 (L-N/N-PE): kA 12.5
Maximum discharge current (IEC) Imax 8/20 (L-N/N-PE): kA 50
Rated discharge current (IEC) In 8/20 (L-N/N-PE): kA 20
Voltage protection level (IEC) Up (L-N/N-PE):
Temporary overvoltage (TOV) resistance Ut (L-N for 5s): V 335
Follow current (IEC) If (N-PE) rms: A No
Tripping time ta (L-N/N-PE): ns
Thermal isolation protection: Da
Backup protection fuse (IEC) with supply line fuse >250A (L-N/N-PE): 250A gG
Maximum short circuit current (IEC) at 50Hz: kA 50
Status indicator - operating / end of life: Frontal indication/Aux contact
Max altitude: m 2000
Mounting: Din rail
Tightening torque for terminals max: Nm 3
Conductor section - Flexible max (IEC): mm² 25
Conductor section - Rigid max (IEC): mm² 35

Greutate: g 600
Frontal IP degree: IP20
Type of contact: CO
Tightening torque for terminals max: Nm 0.25
Conductor section max (IEC): mm² 1.5
Pret: 2.609,64 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/descarcator-tip-1-si-2-modnobloc-iec-impulse-current-iimp-10-350ms-12-5ka-per-pole-4p-cu-contact-comanda-de-la-distanta-126754