www.MATERIALE ELECTRICE.ro
Consiliere specializata



LOVATO DESCARCATOR TIP 2 CU CARTUS, RATED DISCHARGE CURRENT IN (8/20MS) 20KA PER POLE, 2P. CU CONTACT COMANDA DE LA DISTANTA

Cod producator Lovato: Surge Protection Device (SPD)
Tip produs: SG2
Operating voltage type: AC
Application: AC Power lines
Numar de poli: 2P
Number of DIN modules: 2
Relay output: Da
SPD according to IEC/EN 61643-11: Da
Rated operational voltage AC (IEC): VAC 230
Maximum continuous voltage (IEC) Uc: V 300
Maximum discharge current (IEC) Imax 8/20 (L-N/N-PE): kA 50
Rated discharge current (IEC) In 8/20 (L-N/N-PE): kA 20
Voltage protection level (IEC) Up (L-N/N-PE):
Temporary overvoltage (TOV) resistance Ut (L-N for 5s): V 337
Follow current (IEC) If (N-PE) rms: A No
Tripping time ta (L-N/N-PE): ns
Thermal isolation protection: Da
Backup protection fuse (IEC) with supply fuse >315A (L-N/N-PE): 315A / 250A Gg
Maximum short circuit current (IEC) at 50Hz: kA 25 / 50
Status indicator - operating / end of life: Frontal indication/Aux contact
Max altitude: m 2000
Mounting: Din rail
Tightening torque for terminals max: Nm 4.5
Conductor section - Flexible max (IEC): mm² 25
Conductor section - Rigid max (IEC): mm² 35
Greutate: g 266

Frontal IP degree: IP20
Conductor section max (IEC): mm² 1.5
Pret: 408,12 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/descarcator-tip-2-cu-cartus-rated-discharge-current-in-8-20ms-20ka-per-pole-2p-cu-contact-comanda-de-la-distanta-126760