www.MATERIALE ELECTRICE.ro
Consiliere specializata



LOVATO DESCARCATOR TIP 3, WITH PLUG-IN CARTRIDGE, COMBINATION WAVE UOC/ICW (1.2/50 ?S, 8/20?S) 10KV/5KA, 1P+N, CU CONTACT COMANDA DE LA DISTANTA

Cod producator Lovato: Surge Protection Device (SPD)
Tip produs: SA3
Operating voltage type: AC
Application: AC Power lines
Numar de poli: 1P+N
Number of DIN modules: 1
Relay output: Da
SPD according to IEC/EN 61643-11: Da
Rated operational voltage AC (IEC): VAC 230
Maximum continuous voltage (IEC) Uc: V 320
Combined surge (IEC) Uoc/Isc 1,2/50- 8/20 (kV/kA): 10 / 5
Voltage protection level (IEC) Up (L-N/N-PE):
Temporary overvoltage (TOV) resistance Ut (L-N for 5s): V 337
Tripping time ta (L-N/N-PE): ns
Backup protection fuse (IEC) with supply fuse >63A (L-N/N-PE): 63A Gg
Maximum short circuit current (IEC) at 50Hz: kA 10
Status indicator - operating / end of life: Frontal indication/Aux contact
Max altitude: m 2000
Mounting: Din rail
Tightening torque for terminals max: Nm 0.5 (L-N) 3 (PE)
Conductor section - Flexible max (IEC): mm² 4 (L,N) / 25 (PE)
Conductor section - Rigid max (IEC): mm² 6 (L,N) / 35 (PE)
Greutate: g 140
Frontal IP degree: IP20
Conductor section max (IEC): mm² 1.5

Pret: 476,38 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/descarcator-tip-3-with-plug-in-cartridge-combination-wave-uoc-icw-1-2-50-ms-8-20ms-10kv-5ka-1p-n-cu-contact-comanda-de-la-distanta-126770