



WAGO 2-CONDUCTOR DISCONNECT/TEST TERMINAL BLOCK; WITH SHIELD CONTACT; WITH TEST PORT; FOR 2 MM AND 3 MM Ø TEST PLUGS; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM²; CAGE CLAMP®; 2,50 MM²; ORANGE

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Curent nominal: 16; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper; Aluminum;

Solid conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar total de conexiuni: 2;

Total number of potentials: 2;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): 12 AWG: THHN, THWN;

Latime: 5 mm / 0.197 inch;

Inaltime from upper-edge of DIN-rail: 28,5 mm / 1.122 inch;

Adancime: 82 mm / 3.228 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;

Culoare: orange;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,148; MJ

Greutate: 10,2; g

Product Group: 1 (Rail Mounted Terminal Blocks);

Tip ambalare: BOX;

Tara de origine: CN;

GTIN: 4050821180999;

Customs tariff number: 85365080900;

Pret: 21,38 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-disconnect-test-terminal-block-with-shield-contact-with-test-port-for-2-mm-and-3-mm-oe-test-plugs-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-orange-130545>