



**WAGO 4-CONDUCTOR THROUGH TERMINAL BLOCK; 4 MM²; WITH TEST PORT;
WITHOUT SHIELD CONTACT; CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X
7.5; CAGE CLAMP®; 4,00 MM²; ORANGE**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 20; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar total de conexiuni: 4;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 5 mm / 0.197 inch;

Inaltime from upper-edge of DIN-rail: 29 mm / 1.142 inch;

Adancime: 87 mm / 3.425 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Marking level: Center marking;

Culoare: orange;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,175; MJ

Greutate: 10,7; g

Product Group: 1 (Rail Mounted Terminal Blocks);

Tip ambalare: BOX;

Tara de origine: PL;

GTIN: 4044918560795;

Customs tariff number: 85369010000;

Pret: 11,46 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-conductor-through-terminal-block-4-mm2-with-test-port-without-shield-contact-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-4-00-mm2-orange-130675>