
www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 6 MM²; SUITABLE FOR EX E II APPLICATIONS; CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 6,00 MM²; LIGHT GRAY

Ratings per: IEC/EN 60947-7-1;
Curent nominal: 39; A
Tensiune nominala EN (Ex e II): 750; V
Curent nominal (Ex e II): 39; A
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Open Tool Slot;
Connectable conductor materials: Copper;
Solid conductor: 0.2 … 6 mm² / 24 … 10 AWG;
Fine-stranded conductor: 0.2 … 6 mm² / 24 … 10 AWG;
Strip length: 12 … 13 mm / 0.47 … 0.51 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Latime: 8 mm / 0.315 inch;
Inaltime from upper-edge of DIN-rail: 43.5 mm / 1.713 inch;
Adancime: 82.5 mm / 3.248 inch;
Design: angled;
Tip montaj: DIN-35 rail;
Marking level: Center marking;
Culoare: light gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,303; MJ
Greutate: 17; g
Tip ambalare: BOX;

Tara de origine: DE;
GTIN: 4044918583404;
Customs tariff number: 85369010000;
Pret: 11,19 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/2-conductor-through-terminal-block-6-mm2-suitable-for-ex-e-ii-applications-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-6-00-mm2-light-gray-130708