www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO PCB TERMINAL BLOCK; PUSH-BUTTON; 1.5 MM²; PIN SPACING 3.5 MM; 15-POLE; PUSH-IN CAGE CLAMP®; 1,50 MM²; GRAY

Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 250; V
Tensiune nominala de supratensiune (III/3): 4; kV
Tensiune nominala (III/2): 320; V
Tensiune nominala de supratensiune (III/2): 4; kV
Tesiune nominala (II/2): 630; V
Tensiune nominala de supratensiune (II/2): 4; kV
Curent nominal: 17,5; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group B): 300; V
Curent nominal UL (Use Group B): 10; A
Tensiune nominala UL (Use Group C): 150; V
Curent nominal UL (Use Group C): 10; A
Tensiune nominala UL (Use Group D): 300; V
Curent nominal UL (Use Group D): 10; A
Certificari: UL 1059;
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Push-button;
Solid conductor: 0.2 … 1.5 mm² / 24 … 16 AWG;
Fine-stranded conductor: 0.2 … 1.5 mm² / 24 … 16 AWG;
Fine-stranded conductor; with insulated ferrule: 0.25 … 1 mm²;
Fine-stranded conductor; with uninsulated ferrule: 0.25 … 1 mm²;
Strip length: 9 … 10 mm / 0.35 … 0.39 inch;
Conductor connection direction to PCB: 0; °
Numar poli: 15;
Numar total de conexiuni: 15;

Total number of potentials: 15;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Number of test slots: 1;
Distanta intre pini: 3.5 mm / 0.138 inch;
Latime: 54 mm / 2.126 inch;
Inaltime: 13.7 mm / 0.539 inch;
Inaltime de la fata: 10.5 mm / 0.413 inch;
Adancime: 13.6 mm / 0.535 inch;
Lungimea pinului de contact: 3,2; mm
Solder pin dimensions: 0.5 x 0.75 mm;
Diametrul de gaurire cu toleranta: 1.1 (+0.1) mm;
PCB contact: THT;
Solder pin arrangement: over the entire terminal strip, staggered;
Number of solder pins per potential: 2;
Culoare: gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,14; MJ
Greutate: 6,8; g
Temperatura lucru: -60 … +105 °C;
Product Group: 4 (Printed Circuit);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4045454731632;
Customs tariff number: 85369010000;
Pret: 19,29 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/pcb-terminal-block-push-button-1-5-mm2-pin-spacing-3-5-mm-15-pole-push-in-cage-clamp-1-50-mm2-gray-130939