



WAGO 2-CONDUCTOR GROUND TERMINAL BLOCK; 16 MM²; SUITABLE FOR EX E II APPLICATIONS; CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 16,00 MM²; GREEN-YELLOW

Ratings per: IEC/EN 60947-7-2;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Solid conductor: 0,2 ... 16 mm² / 24 ... 6 AWG;
Fine-stranded conductor: 0,2 ... 16 mm² / 24 ... 6 AWG;
Strip length: 16 ... 17 mm / 0.63 ... 0.67 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Latime: 12 mm / 0.472 inch;
Inaltime from upper-edge of DIN-rail: 37,5 mm / 1.476 inch;
Adancime: 94,5 mm / 3.72 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Marking level: Center marking;
Culoare: green-yellow;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,502; MJ
Greutate: 47; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454089290;
Customs tariff number: 85369010000;

Pret: 39,64 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-ground-terminal-block-16-mm2-suitable-for-ex-e-ii-applications-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-16-00-mm2-green-yellow-130981>