



**WAGO THT MALE HEADER; 1.2 X 1.2 MM SOLDER PIN; STRAIGHT; 100%
PROTECTED AGAINST MISMATING; SILVER-PLATED CONTACTS; PIN SPACING
10.16 MM; 6-POLE; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Tensiune nominala (III/2): 1000; V

Tensiune nominala de supratensiune (III/2): 8; kV

Tensiune nominala (II/2): 1000; V

Tensiune nominala de supratensiune (II/2): 8; kV

Curent nominal: 76; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 66; A

Tensiune nominala UL (Use Group C): 300; V

Curent nominal UL (Use Group C): 66; A

Tensiune nominala UL (Use Group D): 600; V

Curent nominal UL (Use Group D): 5; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 66; A

Tensiune nominala CSA (Use Group C): 300; V

Curent nominal CSA (Use Group C): 66; A

Tensiune nominala CSA (Use Group D): 600; V

Curent nominal CSA (Use Group D): 5; A

Numar poli: 6;

Total number of potentials: 6;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;
Distanta intre pini: 10,16 mm / 0.4 inch;
Latime: 62,26 mm / 2.451 inch;
Inaltime: 36 mm / 1.417 inch;
Inaltime de la fata: 32 mm / 1.26 inch;
Adancime: 16,5 mm / 0.65 inch;
Lungimea pinului de contact: 4; mm
Solder pin dimensions: 1,2 x 1,2 mm;
Diametrul de gaurire cu toleranta: 1,7 (+0,1) mm;
Tip contact (pluggable connector): Conector tata/fisa;
Connector (connection type): for PCB;
Mismating protection: Yes;
Mating direction to the PCB: 90; °
PCB contact: THT;
Solder pin arrangement: over the entire male connector (in-line);
Number of solder pins per potential: 3;
Culoare: light gray;
Material group: I;
Material izolator: Polybutylene terephthalate (PBT);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: silver-plated;
Greutate: 31,7; g
Temperatura lucru: -60 ... +120 °C;
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143735407;
Customs tariff number: 85366990990;
Pret: 50,97 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tht-male-header-1-2-x-1-2-mm-solder-pin-straight-100-protected-against-mismating-silver-plated-contacts-pin-spacing-10-16-mm-6-pole-light-gray-131140>