
www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO STACKABLE 2-CONDUCTOR PCB TERMINAL BLOCK; 0.75 MM²; PIN SPACING 5/5.08 MM; 1-POLE; PUSH WIRE®; 0,75 MM²; GRAY

Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 250; V
Tensiune nominala de supratensiune (III/3): 4; kV
Tensiune nominala (III/2): 320; V
Tensiune nominala de supratensiune (III/2): 4; kV
Tesiune nominala (II/2): 630; V
Tensiune nominala de supratensiune (II/2): 4; kV
Curent nominal: 10; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group B): 300; V
Curent nominal UL (Use Group B): 10; A
Tensiune nominala UL (Use Group D): 300; V
Curent nominal UL (Use Group D): 10; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group B): 300; V
Curent nominal CSA (Use Group B): 10; A
Tehnologie conexiune: PUSH WIRE®;
Tip actionare: Operating tool;
Solid conductor: 0.25 … 0.75 mm² / 24 … 18 AWG;
Fine-stranded conductor; with uninsulated ferrule: 0.25 … 0.34 mm²;
Strip length: 9 … 10 mm / 0.35 … 0.39 inch;
Conductor connection direction to PCB: 0; °
Numar poli: 1;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar tipuri de conexiuni: 1;

Numar nivele: 1;
Distanta intre pini: 5/5.08 mm / 0.197/0.2 inch;
Latime: 6.5 mm / 0.256 inch;
Inaltime: 12.8 mm / 0.504 inch;
Inaltime de la fata: 9.2 mm / 0.362 inch;
Adancime: 12.5 mm / 0.492 inch;
Lungimea pinului de contact: 3,6; mm
Solder pin dimensions: 0.8 x 0.4 mm;
Diametrul de gaurire cu toleranta: 1 (+0.1) mm;
PCB contact: THT;
Solder pin arrangement: within the terminal block, in line;
Number of solder pins per potential: 2;
Culoare: gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,011; MJ
Greutate: 0,7; g
Temperatura lucru: -60 … +105 °C;
Product Group: 4 (Printed Circuit);
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4044918831703;
Customs tariff number: 85369010000;
Pret: 1,36 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/stackable-2-conductor-pcb-terminal-block-0-75-mm2-pin-spacing-5-5-08-mm-1-pole-push-wire-0-75-mm2-gray-131143