



**WAGO TRIPLE-DECK TERMINAL BLOCK; THROUGH/THROUGH/THROUGH  
TERMINAL BLOCK; WITH ADDITIONAL JUMPER POSITION ON LOWER LEVEL;  
FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM<sup>2</sup>; CAGE CLAMP®; 2,50 MM<sup>2</sup>;  
GRAY/GRAY/BLUE**

Ratings per: IEC/EN 60947-7-1;  
Tensiune nominala (III/3): 500; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Curent nominal: 20; A  
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper; Aluminum;  
Solid conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
Numar total de conexiuni: 6;  
Total number of potentials: 3;  
Numar nivele: 3;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): 12 AWG: THHN, THWN;  
Latime: 5 mm / 0.197 inch;  
Inaltime from upper-edge of DIN-rail: 76,5 mm / 3.012 inch;  
Adancime: 113 mm / 4.449 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Marking level: Center marking;  
Culoare: gray/gray/blue;  
Material izolator: Polyamide 66 (PA 66);

Greutate: 18,5; g  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4055143562928;  
Customs tariff number: 85369010000;  
Pret: 24,69 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/triple-deck-terminal-block-through-through-through-terminal-block-with-additional-jumper-position-on-lower-level-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-gray-gray-blue-131329>