



WAGO DOUBLE-DECK TERMINAL BLOCK; THROUGH/THROUGH TERMINAL BLOCK; N/L; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 1.5 MM²; CAGE CLAMP®; 1,50 MM²; GRAY

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 18; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,08 ... 1,5 mm² / 28 ... 16 AWG;

Fine-stranded conductor: 0,08 ... 1,5 mm² / 28 ... 16 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar total de conexiuni: 4;

Total number of potentials: 2;

Numar nivele: 2;

Wiring type: Front-entry wiring;

Latime: 4 mm / 0.157 inch;

Inaltime from upper-edge of DIN-rail: 39 mm / 1.535 inch;

Adancime: 85 mm / 3.346 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Potential marking: N/L;

Marking level: Side marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,145; MJ

Greutate: 7,6; g
Product Group: 1 (Rail Mounted Terminal Blocks);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4050821109358;
Customs tariff number: 85369010000;
Pret: 11,58 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/double-deck-terminal-block-through-through-terminal-block-n-l-for-din-rail-35-x-15-and-35-x-7-5-1-5-mm2-cage-clamp-1-50-mm2-gray-131379>