



**WAGO 2-CONDUCTOR GROUND TERMINAL BLOCK; 10 MM<sup>2</sup>; SUITABLE FOR EX E II APPLICATIONS; CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 10,00 MM<sup>2</sup>; GREEN-YELLOW**

Ratings per: IEC/EN 60947-7-2;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Open Tool Slot;  
Connectable conductor materials: Copper;  
Solid conductor: 0,2 ... 10 mm<sup>2</sup> / 24 ... 8 AWG;  
Fine-stranded conductor: 0,2 ... 10 mm<sup>2</sup> / 24 ... 8 AWG;  
Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;  
Solid conductor 2: 0,2 ... 16 mm<sup>2</sup> / 24 ... 6 AWG;  
Fine-stranded conductor 2: 0,2 ... 16 mm<sup>2</sup> / 24 ... 6 AWG;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Latime: 10 mm / 0.394 inch;  
Inaltime from upper-edge of DIN-rail: 43,5 mm / 1.713 inch;  
Adancime: 82,5 mm / 3.248 inch;  
Design: angled;  
Tip montaj: DIN-35 rail;  
Marking level: Center marking;  
Culoare: green-yellow;  
Material izolator: Polyamide 66 (PA 66);  
Greutate: 33,7; g  
Product Group: 17 (TOP JOB installation terminal blocks);  
Tip ambalare: BOX;  
Tara de origine: DE;

GTIN: 4045454092795;  
Customs tariff number: 85369010000;  
Pret: 32,47 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-ground-terminal-block-10-mm2-suitable-for-ex-e-ii-applications-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-10-00-mm2-green-yellow-131523>