



WAGO SNAP-IN SOCKET; 2-POLE; COD. B; 1,50 MM²; GRAY

Note on Contact Resistance: approx. 1 m² of contact resistance approx. 0.25 m² contact transition plug/socket;

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Curent nominal: 16; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL 1977: 600; V

Curent nominal UL 1977: 14; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Operating tool; Push-in;

Nominal cross-section: 1,5 mm²;

Solid conductor: 0,25 ... 1,5 mm² / 22 ... 16 AWG;

Solid conductor; push-in termination: 0,75 ... 1,5 mm² / 20 ... 16 AWG;

Stranded conductor: 0,25 ... 1 mm² / 22 ... 18 AWG;

Fine-stranded conductor: 0,25 ... 1,5 mm² / 22 ... 16 AWG;

Fine-stranded conductor; with insulated ferrule: 0,25 ... 0,75 mm² / 22 ... 20 AWG;

Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 0,75 mm² / 22 ... 20 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 0,75 mm² / 20 AWG;

Strip length: 9 mm / 0.35 inch;

Note (strip length): see also packaging or instructions;

Numar poli: 2;

Numar total de conexiuni: 2;

Total number of potentials: 2;

Conductor entry direction to mating direction: 0; °

Distanta intre pini: 4,4 mm / 0.173 inch;

Latime: 19,8 mm / 0.78 inch;

Inaltime: 16 mm / 0.63 inch;
Adancime: 39,85 mm / 1.569 inch;
Coding: B;
Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);
Retention force of a plug-in connection: Locked: > 80 N;
Unmating force of a plug-in connection: Unlocked: approx. 20 ... 70 N (depending on pole number);
Number of mating cycles: ?200, without resistive load100, with resistive load IN = 16 A, tested (1.5 mm²/16 AWG);
Housing sheet thickness: 0,5 ... 2 mm / 0.02 ... 0.079 inch;
Tip montaj: Snap-in;
Marking: L N;
Protection type: IP40;
Potential marking: L N;
Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for conductor;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: yes;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Copper or copper alloy (surface-treated);
Fire load: 0,107; MJ
Greutate: 4,5; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: Insulating parts for temperatures ? 105 °C;
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4055143428217;
Customs tariff number: 85366990990;
Pret: 11,15 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/snap-in-socket-2-pole-cod-b-1-50-mm2-gray-132098>