



WAGO 4-CONDUCTOR/2-PIN DOUBLE-DECK CARRIER TERMINAL BLOCK; 4-CONDUCTOR/2-PIN THROUGH TERMINAL BLOCK; L/L; INTERNAL COMMONING; CONDUCTOR ENTRY WITH VIOLET MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM²; CAGE CLAMP®; 2,50 MM²; GRAY

Tensiune nominala (III/3): 500; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 16; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Open Tool Slot;
Connectable conductor materials: Copper;
Solid conductor: 0.08 ... 2.5 mm² / 28 ... 12 AWG;
Fine-stranded conductor: 0.08 ... 4 mm² / 28 ... 12 AWG;
Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;
Numar total de conexiuni: 6;
Total number of potentials: 1;
Numar nivele: 2;
Wiring type: Front-/Side-entry wiring;
Latime: 5 mm / 0.197 inch;
Inaltime from upper-edge of DIN-rail: 39.8 mm / 1.567 inch;
Adancime: 91 mm / 3.583 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Potential marking: L;
Marking level: Side marking;
Culoare: gray;
Greutate: 13,8; g
Tip ambalare: BOX;

Tara de origine: DE;
GTIN: 4055143614269;
Customs tariff number: 85366990990;
Pret: 20,89 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/4-conductor-2-pin-double-deck-carrier-terminal-block-4-conductor-2-pin-through-terminal-block-1-1-internal-commoning-conductor-entry-with-violet-marking-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-gray-132215>