



WAGO SPACE-SAVING, 2-CONDUCTOR END TERMINAL BLOCK; WITHOUT PUSH-BUTTONS; WITHOUT PROTRUDING SNAP-IN MOUNTING FOOT; FOR TERMINAL STRIPS WITH SNAP-IN MOUNTING FEET; 4 MM²; CAGE CLAMP®; 4,00 MM²; ORANGE

Tensiune nominala (III/3): 630; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0.08 ... 4 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0.08 ... 4 mm² / 28 ... 12 AWG;

Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Latime: 7 mm / 0.276 inch;

Inaltime de la fata: 23 mm / 0.906 inch;

Adancime: 33.5 mm / 1.319 inch;

Design: horizontal;

Tip montaj: Snap-in mounting foot;

Marking level: Side marking;

Culoare: orange;

Fire load: 0,077; MJ

Greutate: 4,2; g

Product Group: 9 (Std. Chassis Mt. Blocks);

Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4044918640596;
Customs tariff number: 85369010000;
Pret: 3,68 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/space-saving-2-conductor-end-terminal-block-without-push-buttons-without-protruding-snap-in-mounting-foot-for-terminal-strips-with-snap-in-mounting-feet-4-mm2-cage-clamp-4-00-mm2-orange-132594>