
www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO 3-WAY DISTRIBUTION CONNECTOR; 4-POLE; COD. B; 1 INPUT; 3 OUTPUTS; PINK

Note on Contact Resistance: approx. 1 m? of contact resistance approx. 0.25 m? contact transition plug/socket;
Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 400; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 16; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tensiune nominala UL 1977: 600; V
Curent nominal UL 1977: 12; A
Numar poli: 4;
Total number of potentials: 4;
Distanta intre pini: 4,4 mm / 0.173 inch;
Latime: 20,8 mm / 0.819 inch;
Inaltime: 32,65 mm / 1.285 inch;
Adancime: 63,5 mm / 2.5 inch;
Coding: B;
Mating force of a plug-in connection: approx. 20 … 70 N (depending on pole number);
Retention force of a plug-in connection: When locked: > 80 N;
Unmating force of a plug-in connection: when unlocked: approx. 20 … 70 N (depending on pole number);
Number of mating cycles: ?200, without resistive load100, with resistive load IN = 16 A, tested (1.5 mm²/16 AWG);
Distributor type: Distribution connector, 3-way,;
Marking: 1 2 3 4;
Protection type: IP20;
Note on protection type: IP40 when mated;
Potential marking: 1 2 3 4;

Tip contact (pluggable connector): Socket/plug;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: yes;
Culoare: pink;
Material izolator: Polyamide 66 (PA 66);
Contact material: Copper or copper alloy (surface-treated);
Fire load: 0,507; MJ
Greutate: 22,3; g
Processing temperature: -5 … +40 °C;
Continuous operating temperature: -35 … +85 °C;
Note on continuous operating temperature: Insulating parts for temperatures ? 105 °C;
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4050821876403;
Customs tariff number: 85366990990;
Pret: 55,59 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/3-way-distribution-connector-4-pole-cod-b-1-input-3-outputs-pink-132732