



WAGO THR PCB TERMINAL BLOCK; PUSH-BUTTON; 1.5 MM²; PIN SPACING 3.5 MM; 6-POLE; PUSH-IN CAGE CLAMP®; IN TAPE-AND-REEL PACKAGING; 1,50 MM²; BLACK

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 200; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 320; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 17,5; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 10; A

Tensiune nominala UL (Use Group C): 150; V

Curent nominal UL (Use Group C): 10; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-button;

Solid conductor: 0,2 ... 1,5 mm² / 24 ... 16 AWG;

Fine-stranded conductor: 0,2 ... 1,5 mm² / 24 ... 16 AWG;

Fine-stranded conductor; with insulated ferrule: 0,25 ... 1 mm²;

Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 1 mm²;

Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;

Conductor connection direction to PCB: 0; °

Numar poli: 6;

Numar total de conexiuni: 6;
Total number of potentials: 6;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 3,5 mm / 0.138 inch;
Latime: 22,5 mm / 0.886 inch;
Inaltime: 12,7 mm / 0.5 inch;
Inaltime de la fata: 10,5 mm / 0.413 inch;
Adancime: 13,6 mm / 0.535 inch;
Lungimea pinului de contact: 2,2; mm
Solder pin dimensions: 0,5 x 0,75 mm;
Diametru placat prin gaura (THR): 1,1 (+0,1) mm;
Reel diameter of tape-and-reel packaging: 330; mm
Tape Latime: 44; mm
PCB contact: THR;
Solder pin arrangement: over the entire terminal strip (staggered);
Number of solder pins per potential: 2;
Culoare: black;
Material group: III a;
Material izolator: Polyamide 46 (PA 46);
Flammability class per UL94: V2;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Greutate: 3,8; g
Temperatura lucru: -60 ... +105 °C;
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4050821890492;
Customs tariff number: 85369010000;
Pret: 10,91 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/thr-pcb-terminal-block-push-button-1-5-mm2-pin-spacing-3-5-mm-6-pole-push-in-cage-clamp-in-tape-and-reel-packaging-1-50-mm2-black-132803>