



WAGO PRE-ASSEMBLED CONNECTING CABLE; ECA; PLUG/OPEN-ENDED; 5-POLE;
COD. I; H05Z1Z1-F 3G 1.5 MM²; 4M; 1,50 MM²; BLUE

Note on Contact Resistance: approx. 1 m² of contact resistance approx. 0.25 m² contact transition plug/socket;

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL 1977: 600; V

Curent nominal UL 1977: 23; A

Strip length: 9 mm / 0.35 inch;

Numar poli: 5;

Total number of potentials: 3;

Ground function: with preceding ground contact;

Conductor preparation: tip-bonded;

Sheathed cable diameter: 7,4 ... 9,4 mm;

Sectiunea transversala a firului: 1,5; mm²

Strip length (outer insulation): 48; mm

Connection type: Plug - Free end;

Distanta intre pini: 10 mm / 0.394 inch;

Total length: 4; m

Technologie: DALI;

Coding: I;

Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);

Retention force of a plug-in connection: when locked: > 80N;

Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);

Number of mating cycles: 200 (without resistive load) 100 (with resistive load IN = 25 A), tested (4 mm²);

Connection type: Plug - free end;

Type of pre-assembled cable: Connecting cable;

Cable type: H05Z1Z1-F 3G1.5;

Protection type: IP20;

Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;

Application: Lighting management;

Mismating protection: Yes;

Locking of plug-in connection: locking lever;

Locking lever: retrofittable;

Culoare: blue;

Material izolator: Polyamide 66 (PA 66);

Fire class per EN 50575: Eca;

Contact material: Copper or copper alloy (surface-treated);

Fire load: 119,968; MJ

Connector Culoare: blue;

Halogen-free: Yes;

Greutate: 418,4; g

Processing temperature: -5 ... +40 °C;

Continuous operating temperature: -35 ... +85 °C;

Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free)

Insulating parts for temperatures ? 105 °C;

Tip ambalare: not packed;

Tara de origine: DE;

GTIN: 4055143261135;

Customs tariff number: 85444290900;

Pret: 95,57 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/pre-assembled-connecting-cable-eca-plug-open-ended-5-pole-cod-i-h05z1z1-f-3g-1-5-mm2-4m-1-50-mm2-blue-132811>