





WAGO T-DISTRIBUTION CONNECTOR; 5-POLE; COD. P; 1 INPUT; 2 OUTPUTS; OUTPUTS ON BOTH SIDES; 3 LOCKING LEVERS; FOR FLYING LEADS; RED

Note on Contact Resistance: approx. 1 m? of contact resistance approx. 0.25 m? contact transition

plug/socket;

Ratings per: IEC/EN 60664-1; Tesiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 25; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL 1977: 600; V Curent nominal UL 1977: 23; A

Numar poli: 5;

Total number of potentials: 5;

Ground function: with preceding ground contact;

Distanta intre pini: 10 mm / 0.394 inch;

Latime: 54 mm / 2.126 inch; Inaltime: 36,1 mm / 1.421 inch; Adancime: 48,9 mm / 1.925 inch;

Coding: P;

Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);

Retention force of a plug-in connection: When locked: > 80 N;

Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);

Number of mating cycles: ?200, without resistive load 100, with resistive load IN = 25 A, tested (4

mm²/AWG 12);

Distributor type: T-distribution connector;

Marking: N? L1 L2 L3; Protection type: IP20;

Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily

accessible areas).;

Potential marking: N? L1 L2 L3;

Application: Computer applications (UPS);

Suitable: for flying leads;

Tip contact (pluggable connector): Socket/plug;

Mismating protection: Yes;

Locking of plug-in connection: locking lever;

Locking lever: yes;

Culoare: red;

Material izolator: Polyamide 66 (PA 66);

Contact material: Copper or copper alloy (surface-treated);

Fire load: 0,491; MJ Greutate: 25,4; g

Processing temperature: -5 ... +40 °C;

Continuous operating temperature: -35 ... +85 °C;

Note on continuous operating temperature: Insulating parts for temperatures ? 105 °C;

Product Group: 20 (WINSTA);

Tip ambalare: BOX; Tara de origine: DE; GTIN: 4045454900595;

Customs tariff number: 85366990990;

Pret: 40,99 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/t-distribution-connector-5-pole-cod-p-1-input-2-outputs-outputs-on-both-sides-3-locking-levers-for-flying-leads-red-133024