www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO 1-CONDUCTOR FEMALE PLUG; 100% PROTECTED AGAINST MISMATING; LOCKING LEVER; DIRECT MARKING; 10 MM²; PIN SPACING 7.62 MM; 7-POLE; 10,00 MM²; LIGHT GRAY

Ratings per: IEC/EN 60664-1;
Tesiune nominala (III/3): 800; V
Tensiune nominala de supratensiune (III/3): 8; kV
Tensiune nominala (III/2): 1000; V
Tensiune nominala de supratensiune (III/2): 8; kV
Tesiune nominala (II/2): 1000; V
Tensiune nominala de supratensiune (II/2): 8; kV
Curent nominal: 41; A
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group C): 600; V
Curent nominal UL (Use Group C): 42; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group C): 600; V
Curent nominal CSA (Use Group C): 41; A
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Operating tool;
Solid conductor: 0,5 … 10 mm² / 20 … 8 AWG;
Fine-stranded conductor: 0,5 … 10 mm² / 20 … 8 AWG;
Fine-stranded conductor; with insulated ferrule: 0,5 … 6 mm²;
Fine-stranded conductor; with uninsulated ferrule: 0,5 … 6 mm²;
Strip length: 13 … 15 mm / 0.51 … 0.59 inch;
Numar poli: 7;
Numar total de conexiuni: 7;
Total number of potentials: 7;
Numar tipuri de conexiuni: 1;

Numar nivele: 1;
Distanta intre pini: 7,62 mm / 0.3 inch;
Latime: 80,02 mm / 3.15 inch;
Inaltime: 27,5 mm / 1.083 inch;
Adancime: 41,9 mm / 1.65 inch;
Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for conductors;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Culoare: light gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Material of the additional spring for socket contact: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,84; MJ
Greutate: 54,6; g
Temperatura lucru: -60 … +105 °C;
Product Group: 3 (Multi Conn. System);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4050821240815;
Customs tariff number: 85366990990;
Pret: 66,09 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/1-conductor-female-plug-100-protected-against-mismating-locking-lever-direct-marking-10-mm2-pin-spacing-7-62-mm-7-pole-10-00-mm2-light-gray-133106