





WAGO TAP-OFF MODULE; 3 X 2.5 MM²; 3-POLE; COD. A; FITTED WITH CABLE; WITH STRAIN RELIEF HOUSING; BLACK

Note on Contact Resistance: approx. 1 m? of contact resistance approx. 0.25 m? contact transition

plug/socket;

Ratings per: IEC/EN 60664-1;

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Ground function: with preceding ground contact;

Conductor preparation: tip-bonded;

Sheathed cable diameter: 9,2 ... 11,4 mm;

Total length: 0,44; m

Coding: A;

Mating force of a plug-in connection: approx. 30 ... 70 N (depending on pole number);

Retention force of a plug-in connection: when locked: > 80N;

Unmating force of a plug-in connection: when unlocked: approx. 30 ... 70 N (depending on pole number);

Number of mating cycles: 200 (without resistive load) 100 (with resistive load IN = 25 A), tested (4 mm²);

Marking: L?N; Protection type: IP20;

Note on protection type: Only when mated and secured with a strain relief housing (These compact

connectors are not designed for use in open, easily accessible areas.);

Application: General mains applications; Suitable: for flat cable 3 x 2.5 mm²;

Mismating protection: Yes;

Locking of plug-in connection: locking lever;

Culoare: black:

Material izolator: Polyamide 66 (PA 66);

Fire class per EN 50575: Eca;

Contact material: Copper or copper alloy (surface-treated);

Fire load: 2,767; MJ

Greutate: 160,5; g

Processing temperature: -5 ... +40 °C;

Continuous operating temperature: -35 ... +85 °C;

Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free)

Insulating parts for temperatures ? 105 °C;

Product Group: 20 (WINSTA);

Tip ambalare: BOX; Tara de origine: DE; GTIN: 4045454004279;

Customs tariff number: 85366990990;

Pret: 144,88 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/tap-off-module-3-x-2-5-mm2-3-pole-cod-a-fitted-with-cable-with-strain-relief-housing-black-133469