www.MATERIALE ELECTRICE.ro
Consiliere specializata



WAGO TAP-OFF MODULE; 3 X 2.5 MM²; 3-POLE; COD. A; FITTED WITH CABLE; WITH STRAIN RELIEF HOUSING; BLACK

Note on Contact Resistance: approx. 1 m? of contact resistance approx. 0.25 m? contact transition plug/socket;
Ratings per: IEC/EN 60664-1;
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Ground function: with preceding ground contact;
Conductor preparation: tip-bonded;
Sheathed cable diameter: 9,2 … 11,4 mm;
Total length: 0,44; m
Coding: A;
Mating force of a plug-in connection: approx. 30 … 70 N (depending on pole number);
Retention force of a plug-in connection: when locked: > 80N;
Unmating force of a plug-in connection: when unlocked: approx. 30 … 70 N (depending on pole number);
Number of mating cycles: 200 (without resistive load) 100 (with resistive load IN = 25 A), tested (4 mm²);
Marking: L ? N;
Protection type: IP20;
Note on protection type: Only when mated and secured with a strain relief housing (These compact connectors are not designed for use in open, easily accessible areas.);
Application: General mains applications;
Suitable: for flat cable 3 x 2.5 mm²;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Culoare: black;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: Eca;
Contact material: Copper or copper alloy (surface-treated);
Fire load: 2,767; MJ

Greutate: 160,5; g
Processing temperature: -5 … +40 °C;
Continuous operating temperature: -35 … +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free)
Insulating parts for temperatures ? 105 °C;
Product Group: 20 (WINSTA);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454004279;
Customs tariff number: 85366990990;
Pret: 146,24 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/tap-off-module-3-x-2-5-mm2-3-pole-cod-a-fitted-with-cable-with-strain-relief-housing-black-133469