



**WAGO PRE-ASSEMBLED INTERCONNECTING CABLE; ECA; SOCKET/PLUG; 5-
POLE; COD. B; 4M; 1,50 MM²; PINK**

Note on Contact Resistance: approx. 1 m² of contact resistance approx. 0.25 m² contact transition plug/socket;

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 16; A

Note on Curent nominal: 13 A for 3-pole load 10 A for 4- and 5-pole load;

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL 1977: 600; V

Curent nominal UL 1977: 12; A

Numar poli: 5;

Total number of potentials: 5;

Conductor preparation: tip-bonded;

Sheathed cable diameter: 9,3 ... 11,6 mm;

Sectiunea transversala a firului: 1,5; mm²

Connection type: Socket - Plug;

Distanta intre pini: 4,4 mm / 0.173 inch;

Total length: 4; m

Coding: B;

Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);

Retention force of a plug-in connection: when locked: > 80N;

Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);

Number of mating cycles: ?200, without resistive load 100, with resistive load IN = 16 A, tested (1.5 mm²/16 AWG);

Connection type: Socket - Plug;

Type of pre-assembled cable: Interconnecting cable;

Cable type: Control line 5 x 1.5;
Marking: 1 2 3 4 5;
Protection type: IP20;
Note on protection type: IP40 when mated;
Potential marking: 1 2 3 4 5;
Mismating protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: retrofittable;
Culoare: pink;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: Eca;
Contact material: Copper or copper alloy (surface-treated);
Connector Culoare: pink;
Printing color of mating face: black;
Strain relief Culoare: black;
Printing color of strain relief: white;
Sheathed cable Culoare: gray;
Printing color of sheathed cable: black;
Sheath material: PVC;
Greutate: 676,3; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free)
Insulating parts for temperatures ? 105 °C;
Tip ambalare: not packed;
Tara de origine: PL;
GTIN: 4055143518604;
Customs tariff number: 85444290900;
Pret: 126,70 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/pre-assembled-interconnecting-cable-eca-socket-plug-5-pole-cod-b-4m-1-50-mm2-pink-133754>